

# CONDUIT BODIES • COVERS • GASKETS

Aluminum Die Cast Threaded TB Conduit Bodies for Rigid • IMC conduit



## Applications

To provide access to conductors for pulling, splicing and maintenance

## Features

- Tapered threaded hubs - NPT
- Suitable for use in concrete
- Wet Location

## Standard Materials

Die cast aluminum

Copper free

Covers - Stamped aluminum


Gasket - Neoprene rubber

## Applicable Third Party Standards


- UL Standard: 514A
- Fed. Spec. W-C-586D
- NEMA: FB-1
- UL Listed File # E208392



ATBKON



ATB-CGKON



CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	INNER PACK	MASTER PACK	WEIGHT PER C
Aluminum Die Cast Threaded TB Conduit Bodies							
ATB1KON	1/2	4.750	1.375	2.125	10	100	29.1
ATB2KON	3/4"	5.500	1.563	2.675	10	50	42.3
ATB3KON	1"	6.500	1.813	2.750	5	25	58.2
ATB4KON	1-1/4"	8.250	2.438	3.500	2	10	110.3
ATB5KON	1-1/2"	8.250	2.438	3.500	2	10	108.8
ATB6KON	2"	10.500	3.188	4.500	1	5	192.2
Aluminum Die Cast Threaded TB Conduit Bodies with Stamped Aluminum Cover & Neoprene Gasket							
ATB1CGKON	1/2"	4.750	1.375	2.375	10	100	34.8
ATB2CGKON	3/4"	5.500	1.563	2.625	10	50	49.2
ATB3CGKON	1"	6.500	1.813	3.000	5	25	67.7
ATB4CGKON	1-1/4"	8.250	2.438	3.750	2	10	128.4
ATB5CGKON	1-1/2"	8.250	2.438	3.750	2	10	126.9
ATB6CGKON	2"	10.500	3.188	4.750	1	5	222.5