

## CONDUIT BODIES • COVERS • GASKETS

Aluminum Die Cast Threaded X Conduit Bodies for Rigid • IMC conduit



### Applications

To provide access to conductors for pulling, splicing and maintenance

### Features

- Tapered threaded hubs - NPT
- Suitable for use in concrete
- Wet Location

### Standard Materials


- Die cast aluminum
- Copper free
- Covers - Stamped aluminum
- Gasket - Neoprene rubber

### Applicable Third Party Standards


- UL Standard: 514A
- Fed. Spec. W-C-586D
- NEMA: FB-1
- UL Listed File # E208392



AXKON



AX-CGKON



CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	INNER PACK	MASTER PACK	WEIGHT PER C
Aluminum Die Cast Threaded X Conduit Bodies							
AX1KON	1/2"	4.750	2.688	1.375	10	100	31.4
AX2KON	3/4"	5.500	3.000	1.625	10	50	47.1
AX3KON	1"	6.500	3.500	1.875	5	25	61.9
AX4KON	1-1/4"	8.250	4.500	2.500	2	10	117.7
AX5KON	1-1/2"	8.250	4.500	2.500	2	10	117.9
AX6KON	2"	10.500	5.375	3.375	1	5	212.5
Aluminum Die Cast Threaded X Conduit Bodies with Stamped Aluminum Cover & Neoprene Gasket							
AX1CGKON	1/2"	4.750	2.688	1.625	10	100	37.1
AX2CGKON	3/4"	5.500	3.000	1.875	10	50	54.0
AX3CGKON	1"	6.500	3.500	2.125	5	25	71.4
AX4CGKON	1-1/4"	8.250	4.500	2.750	2	10	135.8
AX5CGKON	1-1/2"	8.250	4.500	2.750	2	10	136.0
AX6CGKON	2"	10.500	5.375	3.625	1	5	242.8