

CONDUIT BODIES • COVERS • GASKETS

Rigid MLL and MLR Conduit Bodies, Malleable Iron for Rigid • IMC conduit



Applications

To provide access to conductors for pulling, splicing and maintenance

Features

- Tapered threaded hubs - NPT
- Suitable for use in concrete

Standard Materials


Malleable iron

Standard Finish


Zinc plated with aluminum enamel paint

Applicable Third Party Standards

- UL Standard: 514A
- Fed. Spec. W-C-586D
- NEMA: FB-1
- UL Listed File # E208392



MLLKON



MLRKON

| CATALOG NUMBER | TRADE SIZE | DIM A | DIM B | DIM C | MASTER PACK | WEIGHT PER C |
|-----------------------------|------------|--------|-------|-------|-------------|--------------|
| Threaded MLL Conduit Bodies | | | | | | |
| MLL1KON | 1/2" | 4.688 | 2.063 | 1.375 | 10 | 87.9 |
| MLL2KON | 3/4" | 5.375 | 2.250 | 1.688 | 10 | 110.3 |
| MLL3KON | 1" | 6.188 | 2.625 | 1.875 | 5 | 160.1 |
| MLL4KON | 1-1/4" | 8.125 | 2.750 | 2.750 | 5 | 346.9 |
| MLL5KON | 1-1/2" | 8.125 | 3.500 | 2.813 | 5 | 369.0 |
| MLL6KON | 2" | 10.500 | 4.125 | 3.313 | 5 | 558.2 |
| MLL7KON | 2-1/2" | 13.625 | 4.688 | 3.875 | 1 | 1211.3 |
| MLL8KON | 3" | 13.875 | 5.875 | 4.750 | 1 | 1542.8 |
| MLL9KON | 3-1/2" | 16.250 | 6.125 | 5.625 | 1 | 2444.0 |
| MLL10KON | 4" | 16.250 | 6.938 | 5.625 | 1 | 2598.2 |
| Threaded MLR Conduit Bodies | | | | | | |
| MLR1KON | 1/2" | 4.688 | 2.063 | 1.375 | 10 | 82.9 |
| MLR2KON | 3/4" | 5.375 | 2.250 | 1.688 | 10 | 115.6 |
| MLR3KON | 1" | 6.188 | 2.625 | 1.875 | 5 | 178.5 |
| MLR4KON | 1-1/4" | 8.125 | 2.750 | 2.750 | 5 | 368.0 |
| MLR5KON | 1-1/2" | 8.125 | 3.500 | 2.813 | 5 | 382.8 |
| MLR6KON | 2" | 10.500 | 4.125 | 3.313 | 5 | 687.1 |
| MLR7KON | 2-1/2" | 13.625 | 4.688 | 3.875 | 1 | 1211.3 |
| MLR8KON | 3" | 13.875 | 5.875 | 4.750 | 1 | 1542.8 |
| MLR9KON | 3-1/2" | 16.250 | 6.125 | 5.625 | 1 | 2487.7 |
| MLR10KON | 4" | 16.250 | 6.938 | 5.625 | 1 | 2667.2 |