

RIGID • IMC

FS and FD Cast Device Boxes



Features

- Tapered threads (NPT with integral bushings)
- Internal grounding screw
- Suitable for use in wet locations when used with FSFDCMIKON cover and FSFDCGKON gasket
- Malleable iron is suitable for concrete use

Standard Materials

Malleable iron

Standard Finish

Zinc plated

Applicable Third Party Standards



- UL Standard: 514A
- NEMA: FB-1
- UL Listed File # E208392



FS Type




FD Type



FSC Type



FDC Type



CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	MASTER PACK	WEIGHT PER C
FSS0KON	1/2"	5.250	2.938	2.125	24	221.9
FS75KON	3/4"	5.250	2.938	2.125	24	233.5
FS100KON	1"	5.250	2.938	2.125	24	242.8
FD50KON	1/2"	5.250	3.000	2.875	16	278.1
FD75KON	3/4"	5.250	3.000	2.875	16	272.8
FD100KON	1"	5.250	3.000	2.875	16	283.7
FSC50KON	1/2"	6.063	2.938	2.125	24	234.4
FSC75KON	3/4"	6.063	2.938	2.125	24	240.6
FSC100KON	1"	6.063	2.938	2.125	24	250.2
FDC50KON	1/2"	6.063	3.000	2.875	16	313.1
FDC75KON	3/4"	6.063	3.000	2.875	16	93.8
FDC100KON	1"	6.063	3.000	2.875	16	305.6

Aluminum available upon request