

# RIGID • IMC

## Double Gang FS and FD Cast Device Boxes



### Features

- Tapered threads (NPT with integral bushings)
- Two grounding screws located on top for easy access
- Suitable for use in wet locations when used with S1002GKON or S1002KON cover and GASK434KON gasket
- Gray iron is suitable for concrete use

### Standard Materials

Gray iron

### Standard Finish

Zinc plated

### Applicable Third Party Standards


- UL 514A
- NEMA: FB-1
- UL Listed File # E208392



FS Type




FDK Type



FSC Type



FDC Type



CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	MASTER PACK	WEIGHT PER C
FS12KON	1/2"	5.125	4.625	2.063	1	297.0
FS22KON	3/4"	5.125	4.625	2.063	1	300.1
FS32KON	1"	5.125	4.625	2.063	1	316.6
FD12KON	1/2"	5.125	4.625	2.875	1	368.6
FD22KON	3/4"	5.125	4.625	2.875	1	375.0
FD32KON	1"	5.125	4.625	2.875	1	376.1
FSC12KON	1/2"	5.938	4.625	2.063	1	301.6
FSC22KON	3/4"	5.938	4.625	2.063	1	315.1
FSC32KON	1"	5.938	4.625	2.063	1	335.2
FDC12KON	1/2"	5.938	4.625	2.875	1	405.1
FDC22KON	3/4"	5.938	4.625	2.875	1	385.1
FDC32KON	1"	5.938	4.625	2.875	1	417.6

Aluminum available upon request