

RIGID • IMC

Conduit Nipples for Rigid Conduit • IMC Malleable Iron



Applications

- Use through knockout to connect box to conduit coupling
- Use with a locknut to connect two boxes side by side or back to back
- Use with a locknut to connect fixture housing to continuous runs

Features

- Threaded NPSM for Rigid conduit & IMC
- RoHS compliant

Standard Materials

Steel screw machined in 1/2" size
Malleable iron in sizes 3/4" thru 6"

Standard Finish



Zinc plated

Applicable Third Party Standards


- UL Standard: 514B
- Fed. Spec. W-F-408E
- NEMA: FB-1
- UL Listed File # E207875



Non-Insulated



Insulated



CATALOG NUMBER	TRADE SIZE	KO SIZE	DIM A	DIM B	INNER PACK	MASTER PACK	WEIGHT PER C
Conduit Nipples for Rigid Conduit and IMC Malleable Iron							
N50KON	1/2"	1/2"	1.125	0.563	100	1000	5.5
N75KON	3/4"	3/4"	1.438	0.750	100	1000	7.7
N100KON	1"	1"	1.750	0.813	50	500	14.6
N125KON	1-1/4"	1-1/4"	2.063	1.125	25	250	24.3
N150KON	1-1/2"	1-1/2"	2.313	1.125	–	25	28.7
N200KON	2"	2"	2.875	1.250	–	25	37.5
N250KON	2-1/2"	2-1/2"	3.563	1.438	–	15	70.5
N300KON	3"	3"	4.375	1.563	–	10	123.5
N350KON	3-1/2"	3-1/2"	4.750	1.625	–	10	163.1
N400KON	4"	4"	4.875	1.688	–	10	198.4
N500KON	5"	5"	6.000	2.125	–	5	330.7
N600KON	6"	6"	7.000	2.250	–	5	440.9
Conduit Nipples for Rigid Conduit and IMC Malleable Iron with insulated throats							
N50-ICKON	1/2"	1/2"	1.125	0.688	100	1000	5.6
N75-ICKON	3/4"	3/4"	1.438	0.813	100	1000	7.8
N100-ICKON	1"	1"	1.750	0.875	50	500	14.8
N125-ICKON	1-1/4"	1-1/4"	2.063	1.188	25	250	24.6
N150-ICKON	1-1/2"	1-1/2"	2.313	1.188	–	25	29.1
N200-ICKON	2"	2"	2.875	1.31	–	25	38.1
N250-ICKON	2-1/2"	2-1/2"	3.563	1.5	–	15	71.7
N300-ICKON	3"	3"	4.375	1.625	–	10	125.4
N350-ICKON	3-1/2"	3-1/2"	4.750	1.688	–	10	165.8
N400-ICKON	4"	4"	4.875	1.813	–	10	201.6
N500-ICKON	5"	5"	6.000	2.188	–	5	336.0
N600-ICKON	6"	6"	7.000	2.375	–	5	448.0