

## CONDUIT BODIES • COVERS • GASKETS

### Raised Dome Stamped Steel Covers and Stamped Aluminum Conduit Body Covers



#### Applications

To cover conduit body opening

#### Features

- Raised dome affords additional wiring room
- Captive stainless steel screws

#### Standard Materials


Steel cover  
Stainless steel screws

#### Standard Finish


Stamped aluminum

#### Applicable Third Party Standards

- UL Standard: 514A
- Fed. Spec. W-C-586D
- NEMA: FB-1
- UL Listed File # E208392



**CKON**



**C-ALKON**

#### Raised Dome Stamped Steel

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	MASTER PACK	WEIGHT PER C
C1KON	1/2"	3.875	1.313	0.250	50	4.7
C2KON	3/4"	4.625	1.500	0.313	50	6.3
C3KON	1"	5.313	1.750	0.313	50	10.0
C4KON	1-1/4" – 1-1/2"	7.313	2.500	0.375	50	18.7
C5KON	2"	9.500	3.188	0.500	25	37.5
C6KON	2-1/2" – 3"	12.250	4.313	3.750	10	65.0
C7KON	3-1/2" – 4"	14.875	5.625	0.750	5	110.0

#### Raised Dome Stamped Aluminum

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	MASTER PACK	WEIGHT PER C
C1-ALKON	1/2"	3.875	1.313	0.1875	50	3.8
C2-ALKON	3/4"	4.688	1.563	0.1875	50	5.1
C3-ALKON	1"	5.375	1.75	0.1875	50	6.6
C4-ALKON	1-1/4" – 1-1/2"	7.313	2.5	0.1875	50	12.6
C5-ALKON	2"	9.5	3.125	0.1875	25	19.9
C6-ALKON	2-1/2" – 3"	12.188	4.5	0.1875	10	50.8
C7-ALKON	3-1/2" – 4"	14.938	5.5	0.1875	5	67.9