

## CONDUIT BODIES • COVERS • GASKETS

Raised Dome Stamped Aluminum/Steel Conduit Body Cover & Neoprene Gasket for Rigid • IMC conduit



### Applications

To provide access to conductors for pulling, splicing and maintenance

### Features

- Tapered threaded hubs - NPT
- Suitable for use in concrete
- NEMA 4 Watertight

### Standard Materials

Copper free  
Covers - Stamped aluminum/steel  
Gasket - Neoprene rubber


### Applicable Third Party Standards

- UL Standard: 514A
- Fed. Spec. W-C-586D
- NEMA: FB-1
- UL Listed File # E208392


U.S. Patent No. 8.129.631



SCGKON



NGKON



### Raised Dome Stamped Aluminum

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	MASTER PACK	WEIGHT PER C
SCG1ALKON	1/2"	3.938	1.375	50	6.3
SCG2ALKON	3/4"	4.688	1.625	50	8.1
SCG3ALKON	1"	5.375	1.875	50	10.0
SCG4ALKON	1-1/4" – 1-1/2"	7.200	2.625	50	18.8
SCG5ALKON	2"	9.563	3.250	25	28.1
SCG6ALKON	2-1/2" – 3"	12.313	4.438	10	60.3
SCG7ALKON	3-1/2" – 4"	14.875	5.688	10	89.7

For use with Form 5 and Form 7  
To order Steel cover, use same part number without "AL"  
Example: SCG1 for Steel cover 1/2"

### Neoprene Rubber Conduit Body Gasket

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	MASTER PACK	WEIGHT PER C
NG1KON	1/2"	3.875	1.313	100	2.5
NG2KON	3/4"	4.688	1.563	100	3.1
NG3KON	1"	5.375	1.750	50	3.2
NG4KON	1-1/4" – 1-1/2"	7.313	2.500	50	6.2
NG5KON	2"	9.500	3.125	25	10.9
NG6KON	2-1/2" – 3"	12.125	4.500	10	12.5
NG7KON	3-1/2" – 4"	15.000	5.500	10	29.7

For use with Form 5 and Form 7