

## EMT

### Steel Compression Connectors for Steel Conduit



#### Features

- Male hub threads - NPSM
- Steel locknuts
- Heavy steel walls
- Concrete tight
- UL listed for Steel & Aluminum EMT Conduit
- RoHS compliant

#### Standard Materials


Nylon  
Steel

#### Standard Finish


Zinc plated

#### Applicable Third Party Standards

- UL Standard: 514B
- Fed. Spec. W-F-408E
- NEMA: FB-1
- UL Listed File # E200730



Non-Insulated



Insulated

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	INNER PACK	MASTER PACK	WEIGHT PER C
Steel Compression Connectors							
CC50RKON	1/2"	0.625	0.500	1.125	50	500	10.6
CC75RKON	3/4"	0.688	0.500	1.375	25	250	17.0
CC100RKON	1"	0.688	0.563	1.688	20	200	22.7
CC125RKON	1-1/4"	0.938	0.688	2.063	10	100	40.6
CC150RKON	1-1/2"	1.063	0.688	2.250	10	100	49.9
CC200RKON	2"	1.125	0.750	2.750	5	50	66.8
CC250RKON	2-1/2"	1.688	0.813	3.625	-	8	176.8
CC300RKON	3"	1.688	0.938	4.250	-	6	234.3
CC350RKON	3-1/2"	1.813	1.000	4.688	-	4	287.3
CC400RKON	4"	1.813	1.000	5.188	-	4	342.6
With Insulated Throat							
CC50-ICRKON	1/2"	0.625	0.500	1.125	50	500	8.7
CC75-ICRKON	3/4"	0.688	0.500	1.375	25	250	12.9
CC100-ICRKON	1"	0.688	0.563	1.688	20	200	20.4
CC125-ICRKON	1-1/4"	0.938	0.688	2.063	10	100	36.0
CC150-ICRKON	1-1/2"	1.063	0.688	2.250	10	100	45.6
CC200-ICRKON	2"	1.125	0.750	2.750	5	50	64.2
CC250-ICRKON	2-1/2"	1.688	0.813	3.625	-	8	131.3
CC300-ICRKON	3"	1.688	0.938	4.250	-	6	141.4
CC350-ICRKON	3-1/2"	1.813	1.000	4.688	-	4	181.8
CC400-ICRKON	4"	1.813	1.000	5.188	-	4	227.3