



EMT

Raintight Compression Connectors

Features

- Male hub threads - NPSM
- Steel locknuts
- Heavy steel walls
- Raintight - Wet locations
- Concrete tight
- Blue nut eases identification
- Suitable for use outdoor
- RoHS compliant

Standard Materials

- Steel
- Neoprene rubber
- Nylon compression ring

Standard Finish

- Zinc plated


Applicable Third Party Standards

- UL Standard: 514B
- Fed. Spec. W-F-408E
- NEMA: FB-1
- UL Listed File # E200730


U.S. Patent No. 8.129.633



Non-Insulated



Insulated



CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	INNER PACK	MASTER PACK	WEIGHT PER C
Raintight Compression Fittings							
CCR-50KON	1/2"	0.625	0.438	1.125	50	500	10.6
CCR-75KON	3/4"	0.688	0.438	1.375	25	250	17.0
CCR-100KON	1"	0.688	0.500	1.688	20	200	22.7
CCR-125KON	1-1/4"	0.938	0.625	2.063	10	100	40.6
CCR-150KON	1-1/2"	1.063	0.625	2.250	10	100	49.9
CCR-200KON	2"	1.125	0.688	2.750	5	50	66.8
CCR-250KON	2-1/2"	1.688	0.750	3.625	-	8	176.8
CCR-300KON	3"	1.688	0.875	4.250	-	6	234.3
CCR-350KON	3-1/2"	1.813	0.938	4.688	-	4	287.3
CCR-400KON	4"	1.813	0.938	5.188	-	4	342.6
With Insulated Throat							
CCR50-ICKON	1/2"	0.625	0.500	1.125	50	500	10.7
CCR75-ICKON	3/4"	0.813	0.500	1.375	25	250	17.1
CCR100-ICKON	1"	0.813	0.563	1.688	20	200	22.9
CCR125-ICKON	1-1/4"	0.938	0.688	2.063	10	100	41.0
CCR150-ICKON	1-1/2"	1.688	0.688	2.250	10	100	50.4
CCR200-ICKON	2"	1.125	0.750	2.750	5	50	67.4
CCR250-ICKON	2-1/2"	1.688	0.813	3.625	-	8	178.1
CCR300-ICKON	3"	1.688	0.938	4.250	-	6	235.7
CCR350-ICKON	3-1/2"	1.813	1.000	4.688	-	4	289.1
CCR400-ICKON	4"	1.813	1.000	5.188	-	4	344.9