

LIQUIDTIGHT

Malleable Liquidtight Fittings - Non-Insulated and Insulated



Features

- Tapered threaded male hub - NPT
- Compact, slim diameter
- Steel locknut
- Liquidtight/Raintight/Oiltight/Concrete tight
- Suitable for wet locations
- Long ferrule prevents pullout & tight bend conduit pop out
- RoHS compliant

Standard Materials

- Malleable iron
- Nylon
- Steel ferrule
- Steel locknut

Standard Finish


- Zinc plated

Applicable Third Party Standards


- UL Standard: 514B
- Fed. Spec. W-F-408E
- NEMA: FB-1
- UL Listed File # E207875



Non-Insulated



Insulated



CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	INNER PACK	MASTER PACK	WEIGHT PER C
Non-Insulated							
LT38KON	3/8"	0.940	0.560	1.190	25	250	15.4
LT50KON	1/2"	0.940	0.630	1.310	25	250	17.6
LT75KON	3/4"	1.060	0.560	1.560	20	200	28.7
LT100KON	1"	1.130	0.690	1.880	10	100	39.7
LT125KON	1-1/4"	1.250	0.690	2.250	5	50	55.1
LT150KON	1-1/2"	1.380	0.690	2.500	4	40	70.5
LT200KON	2"	1.440	0.750	3.000	3	30	99.2
LT250KON	2-1/2"	2.190	1.060	4.060	-	5	363.8
LT300KON	3"	2.500	1.130	4.880	-	5	456.4
LT350KON	3-1/2"	2.690	1.190	5.440	-	5	668.0
LT400KON	4"	3.000	1.250	6.060	-	5	789.2
Insulated							
LT38-ICKON	3/8"	0.938	0.625	1.188	25	250	15.6
LT50-ICKON	1/2"	0.938	0.625	1.313	25	250	17.8
LT75-ICKON	3/4"	1.063	0.625	1.563	20	200	28.9
LT100-ICKON	1"	1.125	0.750	1.875	10	100	40.1
LT125-ICKON	1-1/4"	1.250	0.750	2.250	5	50	55.7
LT150-ICKON	1-1/2"	1.375	0.750	2.500	4	40	71.2
LT200-ICKON	2"	1.438	0.813	3.000	3	30	100.2
LT250-ICKON	2-1/2"	2.188	1.063	4.063	-	5	367.4
LT300-ICKON	3"	2.500	1.250	4.875	-	5	460.9
LT350-ICKON	3-1/2"	2.688	1.313	5.438	-	5	674.7
LT400-ICKON	4"	3.000	1.375	6.063	-	5	797.1

Sizes available up to 6"