

CORD GRIP FITTINGS

Color-Coded Cord Grip Strain Relief Connectors




Applications

To secure and seal cords or cables entering enclosures or raceways

Features

- Neoprene grommet for a moisture proof seal
- Simple installation, cord can be installed without disassembly of the fitting
- Liquidtight/Oiltight/Raintight
- Suitable for NEMA 4 enclosures and other wet locations
- Male tapered thread NPT
- Colored grommet allows for easy identification
- RoHS compliant



Standard Materials

Steel body
Steel gland nut
Neoprene grommet

Applicable Third Party Standards

- UL Standard: 514B
- Fed. Spec. W-F-406E
- UL Listed File # E240397

Standard Finish

Zinc plated body, gland nut

CATALOG NUMBER	TRADE SIZE	COLOR CODE	CABLE RANGE		INNER PACK	MASTER PACK	WEIGHT PER C
			MIN.	MAX.			
CG50-250KON	1/2"	Red	0.15	0.25	25	100	12.3
CG50-350KON	1/2"	White	0.25	0.35	25	100	12.0
CG50-450KON	1/2"	Blue	0.35	0.45	25	100	11.9
CG50-560KON	1/2"	Green	0.45	0.56	25	100	11.8
CG50-650KON	1/2"	Brown	0.55	0.65	25	100	11.3
CG75-250KON	3/4"	Red	0.15	0.25	10	50	18.0
CG75-350KON	3/4"	White	0.25	0.35	10	50	18.0
CG75-450KON	3/4"	Blue	0.35	0.45	10	50	17.8
CG75-560KON	3/4"	Green	0.45	0.56	10	50	17.4
CG75-650KON	3/4"	Brown	0.55	0.65	10	50	17.0
CG75-750KON	3/4"	Yellow	0.65	0.75	10	50	18.3
CG75-850KON	3/4"	Purple	0.75	0.85	10	50	18.1
CG100-560KON	1"	Green	0.45	0.56	5	25	28.1
CG100-650KON	1"	Brown	0.55	0.65	5	25	28.3
CG100-750KON	1"	Yellow	0.65	0.75	5	25	27.4
CG100-850KON	1"	Purple	0.75	0.85	5	25	27.5
CG100-950KON	1"	Gray	0.85	0.95	5	25	28.9
CG100-1050KON	1"	Black	0.95	1.05	5	25	28.6
CG125-850KON	1-1/4"	Purple	0.75	0.85	5	25	45.2
CG125-950KON	1-1/4"	Gray	0.85	0.95	5	25	44.9
CG125-1050KON	1-1/4"	Black	0.95	1.05	5	25	45.0
CG125-1150KON	1-1/4"	Orange	1.05	1.15	5	25	46.8
CG125-1250KON	1-1/4"	Red	1.15	1.25	5	25	45.3
CG125-1375KON	1-1/4"	White	1.25	1.375	5	25	44.5
CG150-1050KON	1-1/2"	Black	0.95	1.05	2	10	70.5
CG150-1150KON	1-1/2"	Orange	1.05	1.15	2	10	69.8
CG150-1250KON	1-1/2"	Red	1.15	1.25	2	10	69.6
CG150-1375KON	1-1/2"	White	1.25	1.375	2	10	68.4

This chart is intended for use as a guide only. Whenever possible, exact cord dimensions should be used. Konkore Fittings™ assumes no liability for errors, omissions or dimensional changes which may result from changes in design, material or the manufacturing process and which may affect cord and fitting compatibility.