

LIQUIDTIGHT

Screw On 45° Connectors for use with Liquidtight Flexible Metallic Conduit • Malleable Iron



Features

- No disassembly required for installation of Screw On Liquidtight
- Tapered threaded male hub - NPT
- Compact, slim diameter
- Liquidtight/Raintight/Oiltight
- Suitable for wet locations
- Long ferrule prevents pullout & tight bend conduit pop out
- RoHS compliant

Standard Materials

- Malleable iron
- Nylon
- Steel ferrule
- Steel locknut

Standard Finish

- Zinc plated


Applicable Third Party Standards

- UL Standard: 514B
- Fed. Spec. W-F-408E
- NEMA: FB-1
- UL Listed File # E207875


U.S. Patent No. 7.914.048



Non-Insulated



Insulated



CATALOG NUMBER	TRADE SIZE	KO SIZE	DIM A	DIM B	DIM C	DIM D	MASTER PACK	WEIGHT PER C
45° Non-Insulated								
LTQ3845KON	3/8"	1/2"	1.938	0.500	1.125	1.500	25	27.1
LTQ5045KON	1/2"	1/2"	2.000	0.500	1.250	1.500	25	27.1
LTQ7545KON	3/4"	3/4"	2.188	0.500	1.563	1.563	10	39.7
LTQ10045KON	1"	1"	2.500	0.625	1.813	1.813	10	63.5
45° Insulated								
LTQ3845-ICKON	3/8"	1/2"	1.938	0.563	1.125	1.5	25	27.3
LTQ5045-ICKON	1/2"	1/2"	2.000	0.563	1.25	1.5	25	27.3
LTQ7545-ICKON	3/4"	3/4"	2.188	0.563	1.563	1.563	10	40.1
LTQ10045-ICKON	1"	1"	2.500	0.688	1.813	1.813	10	64.2

Sizes available up to 2"