

# RIGID • IMC

## Universal Super Connector and 5 piece Coupling

*\*COMING 4TH QUARTER 2016\**

### Applications

Used to join two lengths of conduit; couples conduit when conduit cannot be turned  
 Threaded GRC/IMC to Threaded GRC/IMC  
 Threaded GRC/IMC to Unthreaded GRC/IMC  
 Threaded GRC/IMC to Thin Wall EMT  
 UL Concrete-tight

### Features

- Ease of installation/Quick-connect
- Universal connecting - Threaded to Threaded, Threaded to Unthreaded
- No more turning Pipe
- Self Pipe Alignment
- Eliminates field threading
- Fit GRC/IMC/EMT (Fits all UL approved metal Pipe)

### Standard Materials

Steel

### Standard Finish

Zinc Plated

### Applicable Third Party Standards

- UL us listed UL 514B; C22.2 No. 18.3-12

**U.S. Patent No. 8.586.881**



CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	INNER PACK	WEIGHT PER C
SRCC250KON*	2-1/2"	3.460	3.450	2	2.1
SRCC300KON*	3"	3.490	4.080	1	2.7
SRCC350KON*	3-1/2"	3.730	4.590	1	3.4
SRCC350KON*	4"	3.810	5.090	1	3.9
SRCK250KON*	2-1/2"	4.160	3.450	2	2.3
SRCK300KON*	3"	4.120	4.080	1	2.9
SRCK350KON*	3-1/2"	4.450	4.590	1	3.8
SRCK350KON*	4"	4.500	5.090	1	4.3

\* Not UL Approved

