

RIGID • IMC

Compression Rigid Connectors for Threadless Rigid Conduit • IMC • Malleable Iron



Features

- Concrete tight male hub threads
- NPSM thread 1/2" through 2"
- NPT thread above 2"

Standard Materials

Malleable iron
Steel locknut

Standard Finish


Zinc plated

Applicable Third Party Standards


- UL Standard: 514B
- Fed. Spec. W-F-408E
- NEMA: FB-1
- UL Listed File # E207875



Non-Insulated



Insulated



CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	INNER PACK	MASTER PACK	WEIGHT PER C
Compression Rigid Connectors for Threadless Rigid Conduit & IMC Malleable Iron							
RCC50KON	1/2"	1/2"	1.063	0.688	50	250	23.9
RCC75KON	3/4"	3/4"	1.250	0.688	25	125	25.2
RCC100KON	1"	1"	1.625	0.750	10	50	38.7
RCC125KON	1-1/4"	1-1/4"	2.000	0.813	10	50	58.9
RCC150KON	1-1/2"	1-1/2"	2.313	0.813	5	25	71.6
RCC200KON	2"	2"	2.750	0.875	5	25	118.5
RCC250KON	2-1/2"	2-1/2"	3.313	1.000	2	10	308.5
RCC300KON	3"	3"	4.000	1.000	1	5	331.2
RCC350KON	3-1/2"	3-1/2"	4.375	1.063	1	5	342.8
RCC400KON	4"	4"	5.063	1.125	1	5	469.2
With Insulated Throat							
RCC50-ICKON	1/2"	1.500	0.500	1.500	50	250	23.8
RCC75-ICKON	3/4"	1.500	0.500	1.625	25	125	26.2
RCC100-ICKON	1"	1.690	0.560	2.000	10	50	39.5
RCC125-ICKON	1-1/4"	2.000	0.690	2.375	10	50	56.8
RCC150-ICKON	1-1/2"	2.060	0.690	2.625	5	25	73.6
RCC200-ICKON	2"	2.250	0.880	3.313	5	25	119.7
RCC250-ICKON	2-1/2"	2.940	1.250	3.750	2	10	287.5
RCC300-ICKON	3"	3.130	1.380	4.250	1	5	328.0
RCC350-ICKON	3-1/2"	3.130	1.380	4.750	1	5	346.2
RCC400-ICKON	4"	3.130	1.500	5.313	1	5	484.0