

## RIGID • IMC

### Pull Elbows for Rigid Conduit • IMC



#### Applications

Female to Female: For connecting rigid conduit or IMC to rigid conduit or IMC to form 90° bend

Male to Female: For connecting rigid conduit or IMC to box or enclosures to form 90° bend

#### Features

- Raintight
- Furnished with neoprene gasketed steel cover
- Furnished with steel locknut
- Threaded for Rigid conduit and IMC (Female-NPT, Male-NPSM)

#### Standard Finish

Zinc plated

#### Standard Materials

Body - Malleable iron

Gasket - Neoprene


Cover - Stamped steel

#### Applicable Third Party Standards


- UL Standard: 514B
- NEMA: FB-1
- UL Listed File # E207875



Female to Female



Male to Female



Female to Female 90°

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	INNER PACK	MASTER PACK	WEIGHT PER C
PEF-50KON	1/2"	2.188	2.188	10	100	34.4
PEF-75KON	3/4"	2.313	2.313	5	50	41.5
PEF-100KON	1"	3.000	3.063	—	25	64.4
PEF-125KON	1-1/4"	3.625	3.625	—	20	119.0
PEF-150KON	1-1/2"	4.063	4.063	—	10	176.4
PEF-200KON	2"	4.500	4.500	—	5	268.9

Male to Female 90°

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	INNER PACK	MASTER PACK	WEIGHT PER C
PEM-50KON	1/2"	2.188	2.438	0.563	10	100	42.8
PEM-75KON	3/4"	2.313	2.625	0.625	5	50	53.8
PEM-100KON	1"	3.063	3.188	0.625	—	25	85.9
PEM-125KON	1-1/4"	3.625	4.063	0.750	—	20	136.7
PEM-150KON	1-1/2"	4.063	5.188	0.813	—	10	216.1
PEM-200KON	2"	4.500	5.938	0.938	—	5	347.2