

RIGID • IMC

Set Screw Rigid Couplings Threadless for Rigid Conduit • IMC Malleable Iron



Features

- Concrete tight when taped

Standard Materials



Malleable iron

Standard Finish

Zinc plated

Applicable Third Party Standards

- UL Standard: 514B
- Fed. Spec. W-F-408E
- NEMA: FB-1
- UL Listed File # E207875



RIGID • IMC

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	INNER PACK	MASTER PACK	WEIGHT PER C
RSK50KON	1/2"	1.75	0.78	1.375	20	100	23.6
RSK75KON	3/4"	2	0.875	1.563	20	100	35.1
RSK100KON	1"	2.688	1.188	1.875	5	50	56.0
RSK125KON	1-1/4"	2.75	1.25	2.188	5	25	68.1
RSK150KON	1-1/2"	3.188	1.5	2.5	5	20	91.7
RSK200KON	2"	3.375	1.563	3	2	10	134.7
RSK500KON*^	5"	6	2.813	6.5	—	1	1150.0
RSK600KON*^	6"	6.5	3	7.5	—	1	1400.0

* Furnished with four set screws
 ^ 5" and 6" are NOT UL approved