

Models
AAA,
AA & A


Standard Pulling Grips

(Aluminum Tubing Eye & Copper Tabs)



The following Lewis pulling grips are manufactured in single, double or triple weave configurations (as indicated) of High-Fatigue Aircraft Strand steel cable that is coated with a UV resistant plastic coating. This plastic coating increases the life of the grip, provides a bearing surface on underground pulls and increases the ease and SAFETY of installation and removal for workmen. The Pulling Eye on each Pulling Grip is covered with Aluminum Tubing for a more durable attachment point. Eye can also be ordered with our exclusive Patented, Flexible, Stress relieving, plastic tubing eye for use in less abrasive inner conduit pulls. Copper tabs on tail end of grip add reinforcement to tail end of grip strands and ensure quick loading of product to be pulled.

Model AAA Single or Double Weave – 1/4" to 1/2"



Part No.	Range	Wk.Ld.	Approx. Brk. Stgth.	Weave	Mesh	Eye
AAA-SW-18	1/4" - 1/2"	750 lbs.	1,500 lbs.	single	18"	5 1/2"
AAA-SW-24	1/4" - 1/2"	750 lbs.	1,500 lbs.	single	24"	6"
AAA-DW-18	1/4" - 1/2"	1,700 lbs.	3,500 lbs.	double	18"	5 1/2"
AAA-DW-24	1/4" - 1/2"	1,700 lbs.	3,500 lbs.	double	24"	6"

Model AA Single, Double or Triple Weave – 1/2" to 3/4"



Part No.	Range	Wk.Ld.	Approx. Brk. Stgth.	Weave	Mesh	Eye
AA-SW-18	1/2" - 3/4"	750 lbs.	1,500 lbs.	single	18"	5 1/2"
AA-SW-24	1/2" - 3/4"	750 lbs.	1,500 lbs.	single	24"	6"
AA-DW-18	1/2" - 3/4"	2,000 lbs.	4,000 lbs.	double	18"	5 1/2"
AA-DW-24	1/2" - 3/4"	2,000 lbs.	4,000 lbs.	double	24"	6"
AA-TW-12	1/2" - 3/4"	2,600 lbs.	5,200 lbs.	triple	12"	6"
AA-TW-18	1/2" - 3/4"	2,600 lbs.	5,200 lbs.	triple	18"	6"
AA-TW-24	1/2" - 3/4"	2,600 lbs.	5,200 lbs.	triple	24"	6"
AA-TW-36	1/2" - 3/4"	2,600 lbs.	5,200 lbs.	triple	36"	6"

Model A Single, Double or Triple Weave – 3/4" to 1 1/4"



Part No.	Size Range	Work Load	Approx Brk. Stgth.	Weight	Weave	Mesh Length	Eye
A-SW-18	3/4" - 1 1/4"	1,000 lbs.	3,000 lbs.	5 1/2 oz.	Single	18"	3"
A-SW-24	3/4" - 1 1/4"	1,000 lbs.	3,000 lbs.	5 1/2 oz.	Single	24"	3"
A-DW-18	3/4" - 1 1/4"	2,000 lbs.	6,000 lbs.	8 1/2 oz.	Double	18"	3"
A-DW-24	3/4" - 1 1/4"	2,000 lbs.	6,000 lbs.	8 1/2 oz.	Double	24"	3"
A-TW-18	3/4" - 1 1/4"	3,500 lbs.	10,000 lbs.	12 oz.	Triple	18"	3"
A-TW-24	3/4" - 1 1/4"	3,500 lbs.	10,000 lbs.	12 oz.	Triple	24"	3"