

Flooring, Concrete Repair & Grouting



Loctite® Flooring, Concrete Repair & Grouting Properties Chart

LOCTITE® PRODUCT	ITEM NUMBER	PACKAGE TYPE/SIZE	COLOR	COVERAGE	MIXTURE VISCOSITY (CP)	MAXIMUM TEMPERATURE	COMPRESSIVE STRENGTH (PSI)	WORKING TIME	FUNCTIONAL CURE	MIX RATIO BY VOLUME (RESIN : HARDENER)	MIX RATIO BY WEIGHT (RESIN : HARDENER)	AGENCY APPROVALS		
GROUTS	FIXMASTER® DEEP POUR GROUT	99545	5 gallon kit	Black	660 in. ³	Pourable	225°F	14,500	30 minutes	24 hours	4.1:1 to 8.2 Filler	16.4:3.6 to 80 Filler	CFIA	
	FIXMASTER® FAST SET GROUT	1324134	2 gallon kit	Red	347 in. ³	5,500	200°F	14,500	10 minutes	12 hours	100:11.7	100:6.5	CFIA	
	FIXMASTER® SUPER GROUT	33510	5 gallon kit	Red	620 in. ³	Pourable	225°F	12,900	4.75 hours	24 hours	N/A	10:5 to 85 Aggregate	N/A	
ANCHOR BOLT GROUT	FIXMASTER® ANCHOR BOLT GROUT HP	1108757 1108758	8.6 fl. oz. single cartridge 20.7 fl. oz. dual cartridge	Grey	15.5 in. ³ 37.36 in. ³	N/A	110°F 115°F	9,880	20 minutes	4 hours	100:80	N/A	N/A	
	FIXMASTER® HIGH PERFORMANCE QUARTZ (EXTREME CHEMICAL RESISTANCE)	96495	42 lb. kit	Grey	15 ft. ² (Coverage at 1/4 in. thickness.) 540 in. ³	Semi-Pourable	150°F	12,000	Primer - 45 minutes Topcoat - 60 minutes	24 hours	Primer - 100:61 Topcoat - 100:60 to 282 Filler	N/A	CFIA	
FLOOR REPAIR & RESURFACING	FIXMASTER® FLOOR FILL	99361 99365	10 lb. kit 40 lb. kit	Grey	133 in. ³ 532 in. ³	Semi-Pourable	225°F	15,000	40 minutes	24 hours	4.6:1 to 9.8 Filler	16:3.2 to 80.8 Filler	CFIA	
	FIXMASTER® MAGNA-CRETE™ (WINTER OR SUMMER ADDITIVE REQUIRED, SEE BELOW)	95551 95555 1012500 831304*	1 gallon kit 5 gallon kit 1 lb. 12 oz. kit 2,475 lb. supersack	Grey	170 in. ³ 770 in. ³	N/A	2,000°F	13,000	5 to 20 minutes	1 to 2 hours	N/A	N/A	CFIA	
	FIXMASTER® MAGNA-GROUT™ (WINTER OR SUMMER ADDITIVE REQUIRED, SEE BELOW)	1477079 1476710 1476709*	1 gallon kit 5 gallon kit 2,475 lb. supersack	Grey	170 in. ³ 770 in. ³	N/A	2,000°F	13,000	5 to 20 minutes	1 to 2 hours	N/A	N/A	N/A	
	WINTER ADDITIVE FOR MAGNA-CRETE™ AND MAGNA-GROUT™	40270	1 lb. tub for Winter Use	White	N/A	N/A	2,000°F	13,000	5 to 20 minutes	(+)-10 minutes	N/A	N/A	N/A	
	SUMMER ADDITIVE FOR MAGNA-CRETE™ AND MAGNA-GROUT™	40271	1 lb. tub for Summer Use							(-)-10 minutes				
	FIXMASTER® ACTIVATOR FOR MAGNA-CRETE™ & MAGNA-GROUT™	36334 976786	1 gallon bottle 55 gallon drum	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
	FIXMASTER® CONCRETE REPAIR EPOXY	39366	4 oz. stick	Grey	N/A	Putty	250°F	12,000	4 to 6 minutes	1 hour	N/A	N/A	N/A	
	FIXMASTER® FLEXIBLE JOINT SEALANT	1599979	1 gallon kit	Grey	231 in. ³	17,000	180°F	N/A	30 minutes	6 hours	1:1	N/A	N/A	
	FIXMASTER® CRACK FILLER	1599980	3 gallon kit	Grey	360 in. ³	80,000	180°F	6,170	30 minutes	6 hours	3.5:1	4.3:1	N/A	
	FIXMASTER® CRACK FILLER NS	1108886	8.6 fl. oz. cartridge (one nozzle included)	Grey	15.5 in. ³	Paste	135°F (57°C)	9,800	8 minutes	2 hours	1:1	N/A	N/A	
	FIXMASTER® CRACK FILLER SL	1291113	8.6 fl. oz. cartridge (one nozzle included)	Grey	15.5 in. ³	Flowable	120°F (49°C)	N/A	3 to 6 minutes	90 minutes	1:1	N/A	N/A	
	CHOCKING COMPOUND	FIXMASTER® MARINE CHOCKING	97572 37316 96102	2 gallon kit 1 gallon kit 2 gallon kit	Green Orange	378 in. ³ 132 in. ³ 378 in. ³		250°F	22,000	10 minutes	24 hours	100:11.6	100:6.9	ABS, CFIA ABS, NAVSEA, NEHC

* Uses activator 976786.

Loctite® Flooring, Concrete Repair & Grouting Applications Chart

LOCTITE® PRODUCT	ANCHOR BOLT FASTENING	CHOCKING (SHIPS)	CONCRETE FLOOR REPAIR	NON-SAG CONCRETE REPAIR	ENGINE INSTALLATION	GROUT LIGHT EQUIPMENT 1 IN. OR LESS	GROUT HEAVY EQUIPMENT 1-6 IN.	GROUT HEAVY EQUIPMENT TO 18 IN.	LEVELING EQUIPMENT	ACID/CHEMICAL RESISTANT FLOOR REPAIR	RAMPS & LOADING DOCKS	HIGHWAYS & ROADWAYS	LEVELING FLOORS
FIXMASTER® DEEP POUR GROUT					△	△	▲		△				
FIXMASTER® FAST SET GROUT					△	▲			▲				
FIXMASTER® SUPER GROUT					△		▲	△					
FIXMASTER® ANCHOR BOLT GROUT HP	▲												
FIXMASTER® HIGH PERFORMANCE QUARTZ (EXTREME CHEMICAL RESISTANCE)			△							▲			
FIXMASTER® FLOOR FILL			▲		△					△			
FIXMASTER® MAGNA-CRETE™			▲			△	△				▲	▲	▲
FIXMASTER® MAGNA-GROUT™			▲			△	△				▲	▲	▲
FIXMASTER® CONCRETE REPAIR EPOXY	▲		▲						△	△	▲		
FIXMASTER® FLEXIBLE JOINT SEALANT			▲							▲			
FIXMASTER® CRACK FILLER			▲							▲			
FIXMASTER® CRACK FILLER SL			▲							▲			
FIXMASTER® CRACK FILLER NS				▲									
FIXMASTER® MARINE CHOCKING		▲			▲	△			△				

ITEMS IN RED = Source's PICK or NEW

△ Good Choice ▲ Preferred Choice



Your Source for **FLOOR FILL**
Loctite® Fixmaster® Floor Fill 6-Step Process



Your Source for **CONCRETE REPAIR**
Loctite® Fixmaster® Concrete Repair Epoxy
3-Step Process