

M12™ Grease Gun Kit

2446-21XC (2446-20 Tool-Only)

Specifications:

Output Pressure	Over 8,000 PSI
Run-Time	Up to 7 Grease Cartridges Per Charge
Grease Capacity	14 oz Cartridge, 16 oz Bulk, 16 oz Suction
Air Bleeder Valve	Yes
Weight	7.2 lbs



Includes: (1) M12™ REDLITHIUM™ XC Extended Capacity Battery Pack, 36" Flex Hose with Spring Guard, Grease Coupler, Charger, Carrying Case



M12™ M-SPECTOR FLEX™ 3 ft Inspection Camera Cable Kit


2315-21

Specifications:

Screen Size	3.5" High-Resolution LCD
Camera Resolution	640 x 480
Camera Head Diameter	12.5 mm (0.49")
Cable Length	3 ft
Wireless Distance	Up to 15 ft



Includes: (1) M12™ REDLITHIUM™ Compact Battery Pack, SD Card, USB Cable, Charger, Carrying Case



M12™ M-SPECTOR FLEX™ 3 ft Inspection Camera Cable w/ PIVOTVIEW™ Kit

2317-21

Specifications:

Screen Size	3.5" High-Resolution LCD
Camera Resolution	640 x 480
Camera Head Diameter	12.5 mm (0.49")
Head Movement	Up to 270° PIVOTVIEW™ Camera
Cable Length	3 ft
Wireless Distance	Up to 15 ft



Includes: (1) M12™ REDLITHIUM™ Compact Battery Pack, SD Card, USB Cable, Charger, Carrying Case



M12™ M-SPECTOR FLEX™ Inspection Camera Accessories

Compatible with 2317-21, 2316-21, 2315-21

- 48-53-0155** M-SPECTOR FLEX™ 3 ft Inspection Camera Cable w/ PIVOTVIEW™;
- 48-53-0151** M-SPECTOR FLEX™ 9 ft Inspection Camera Cable;
- 48-53-0150** M-SPECTOR FLEX™ 3 ft Inspection Camera Cable



M12™ M-SPECTOR FLEX™ 9 ft Inspection Camera Cable Kit

2316-21

Specifications:

Screen Size	3.5" High-Resolution LCD
Camera Resolution	640 x 480
Camera Head Diameter	12.5 mm (0.49")
Cable Length	9 ft
Wireless Distance	Up to 15 ft



Includes: (1) M12™ REDLITHIUM™ Compact Battery Pack, SD Card, USB Cable, Charger, Carrying Case



M12™ M-SPECTOR 360™ Rotating Inspection Scope Kit

2313-21 (2313-20 Tool-Only)

Specifications:

Screen Size	2.7" High-Resolution LCD
Display Resolution	320 x 240
Camera Head Diameter	9 mm (0.35")
Cable Length	3 ft
LED Brightness	4 LEDs, 5 Settings



Includes: (1) M12™ REDLITHIUM™ Compact Battery Pack, Hook, Magnet, Mirror Attachments, Charger, Carrying Case

M12™ M-SPECTOR 360™ 9 ft Rotating Inspection Scope Kit

2314-21

Specifications:

Screen Size	2.7" High-Resolution LCD
Display Resolution	320 x 240
Camera Head Diameter	9 mm (0.35")
Cable Length	9 ft
LED Brightness	4 LEDs, 5 Settings



Includes: (1) M12™ REDLITHIUM™ Compact Battery Pack, Hook, Magnet, Mirror Attachments, Pipe Guide, Charger, Carrying Case

M12™ M-SPECTOR 360™ Rotating Inspection Scope Accessories

Compatible with 2313-21, 2314-21

- 48-53-0112** Accessory 3-Pack (Includes Hook, Magnet, Mirror Attachments);
- 48-53-0113** Pipe Guide Accessory



M12™ 102 x 77 Infrared Camera Kit

2258-21

Specifications:

Thermal Resolution	102 x 77
Temperature Range	14°F – 626°F (-10°C – 330°C)
Screen Size	2.4" LCD
Distance-to-Spot Ratio (Center Crosshair)	83:1
Targeting Assistance	Dual Laser
Image Storage & Reporting	Yes



MILWAUKEE® Thermal Imaging Software Available Online

Includes: (1) M12™ REDLITHIUM™ Compact Battery Pack, Rubber Boot, USB Cable, SD Card, Manual, Charger, Soft Carrying Case



M12™ 160 x 120 Thermal Imager Kit

2260-21, NIST Certified 2260-21NST

Specifications:

Thermal Resolution	160 x 120
Temperature Range	14°F – 662°F (-10°C – 350°C)
Temperature Accuracy	±4° F (±2° C)
Visual Camera	Yes
Screen Size	3.5" LCD
Image Storage & Reporting	Yes



MILWAUKEE® Thermal Imaging Software Available Online

Includes: (1) M12™ REDLITHIUM™ Compact Battery Pack, Thermal Imager Report Software, SD Card, USB Cable, SD Card Reader, Quick Reference Card, Statement of Calibration, Charger, Carrying Case



M12™ 12:1 Infrared TEMP-GUN™

2278-20

Specifications:

Distance-to-Spot Ratio	12:1
Temperature Range	-22°F – 1,022°F (-30°C – 550°C)
Basic Accuracy	+/-1.8%
Max/Min/Avg/Dif	Yes
High/Low Alerts	Yes
Emissivity	Fixed, .95
Drop Test	6 ft



Battery and Charger Sold Separately