

CENTER LAP ALUMINUM OXIDE - VITRIFIED BOND

FOR EXCELL-O CENTER LAP AND SIMILAR MACHINES

FEATURES & BENEFITS

- Specially formulated wheel treatment (#5 wood resin) adds lubricity to the wheel, minimizing risk of metallurgical damage
- Larger diameter spindle for minimum deflection, rigid support
- Precise dimensional tolerances ensure accurate location of part centers

TIER: **BETTER**
 BRAND: Norton
 TRADENAME: **CENTER LAP**
 ABRASIVE: Aluminum Oxide

SHAPE	SIZE (D x T)	SPINDLE DIA. †	MAX. RPM*	MIN./STD. PKG.	SPEC	PART #
Center Lap Mounted Points						
–	1/2 x 2**	1/2	65,000	5/25	A80-VVM	61463621421
–	1 x 2**	1/2	15,900	5/25	A80-VVM	61463622926

† Spindle length is 1-1/4"

* Maximum RPM valid to 1/2" overhang. See package insert for other overhangs.

** Pointed 60°

TECH TIP

Dress the center lap mounted points frequently to ensure accurate and smooth center holes.



It is the user's responsibility to refer to and comply with ANSI B7.1

NORTON NORZON ZIRCONIA ALUMINA – RESIN BOND

BEST CHOICE FOR FAST STOCK REMOVAL

FEATURES & BENEFITS

- NZ (NorZon) zirconia alumina self-sharpening abrasive and durable organic bond provide 2X faster stock removal than competitive aluminum oxide products, while lasting 4X longer

NORTON CHARGER Z/A & A/O BLEND – RESIN BOND

BETTER CHOICE FOR FAST STOCK REMOVAL AND LONG LIFE

FEATURES & BENEFITS

- Zirconia alumina/aluminum oxide abrasive blend provides 35% faster cut rate than standard aluminum oxide mounted points
- An aggressive, free cut cleans more parts in less time to substantially increase productivity
- Specially formulated organic bond for 2X greater life than ordinary aluminum oxide mounted points, with reduced vibration and wheel chatter
- Charger mounted point pre-packed in small packages are ideal for vending machines, pegboards, small jobs, and carrying to job site

TIER: **BEST**
 BRAND: Norton
 TRADENAME: **NORZON**
 ABRASIVE: Zirconia Alumina

SHAPE	SIZE (D x T)	SPINDLE DIA. †	MAX. RPM*	MIN./STD. PKG.	SPEC	PART #	SPEC	PART #
Resin Bond Mounted Points								
A1	3/4 x 2-1/2	1/4	19,800	5/25	NZ24-UBXR1	61463616457	Charger	61463616458
A3	1 x 2-3/4	1/4	16,100	5/25	NZ24-UBXR1	61463616459	Charger	61463616460
			16,100	2 V			Charger	66253325924
A5	3/4 x 1-1/8	1/4	45,000	5/25			Charger	61463616462
			45,000	5 V			Charger	66253325926
A11	7/8 x 2	1/4	19,860	5/25	NZ24-UBXR1	61463616463	Charger	61463616464
W189	1/2 x 2	1/4	24,000	5/25	NZ24-UBXR1	61463616465	Charger	61463616466
			24,000	5 V			Charger	66253325928
W197	5/8 x 2	1/4	21,000	5/25	NZ24-UBXR1	61463616467		
W207	3/4 x 1-1/2	1/4	24,000	5/25			Charger	61463616470
W208	3/4 x 2	1/4	18,750	5/25	NZ24-UBXR1	61463616471	Charger	61463616472
W220	1 x 1	1/4	25,500	5/25	NZ24-UBXR1	61463617520	Charger	61463617521
			25,500	5 V			Charger	66253325930
W221	1 x 1-1/2	1/4	19,120	5/25	NZ24-UBXR1	61463616473	Charger	61463616474
W222	1 x 2	1/4	15,900	5/25	NZ24-UBXR1	61463616475	Charger	61463616476

† Spindle length is 1-1/2"

* Maximum RPM valid to 1/2" overhang. See package insert for other overhangs.

V = Vendible package. Ideal for vending machines and small jobs. Min. Pkg. Qty = number of mounted points per vendible pack. Order in multiples of min qty.

