

CRIMPED WIRE

Wheel Brushes

Osborn's crimped wire wheel brushes are filled with steel or stainless steel wire in a variety of gages for applications ranging from aggressive material removal and deburring, to surface conditioning and polishing. Arbor holes are easily adapted to any spindle or drive arbor with Osborn adapters.

CRIMPED WIRE WHEEL BRUSH WITH SHANK

Crimped Wire Wheel Brushes feature uniform, dense fill and can be used off-hand or on drill presses for internal and external cleaning and deburring.

► **APPLICATIONS:** Rust, scale, paint, dirt, weld spatter removal

Brush Dia.	Fill Dia.	Trim Length	Shank Dia.	MSFS (RPM)	Value	Part No.
Steel						
1-1/2	0.008	9/32	1/4	25,000	●●●	0001646300
1-1/2	0.012	9/32	1/4	25,000	●●●	0001646600
1-1/2	0.014	9/32	1/4	25,000	●●●	0001646700
2	0.008	7/16	1/4	25,000	●●●	0001646800
2	0.014	7/16	1/4	25,000	●●●	0001647500
2	0.014	-	1/4	18,500	●○○	0009900100
2	0.020	7/16	1/4	25,000	●●●	0001647800
2-1/2	0.008	11/16	1/4	25,000	●●●	0001648200
2-1/2	0.014	11/16	1/4	25,000	●●●	0001648300
2-1/2	0.020	11/16	1/4	25,000	●●●	0001648600
3	0.008	3/4	1/4	25,000	●●●	0001648800
3	0.008	-	1/4	18,500	●○○	0009900200
3	0.014	3/4	1/4	25,000	●●●	0001649600
3	0.014	-	1/4	18,500	●○○	0009900300
3	0.020	3/4	1/4	25,000	●○○	0001650100
4	0.008	1	1/4	15,000	●●●	0001650200
4	0.014	1	1/4	15,000	●●●	0001650400
Stainless Steel						
1-1/2	0.006	9/32	1/4	25,000	●●●	0001655200
1-1/2	0.012	9/32	1/4	25,000	●●●	0001655400
2	0.008	7/16	1/4	25,000	●●●	0001655500
2	0.008	-	1/4	18,500	●○○	0009900400
2	0.014	7/16	1/4	25,000	●●●	0001655900
2-1/2	0.008	11/16	1/4	25,000	●●●	0001656100
2-1/2	0.014	11/16	1/4	25,000	●●●	0001656200
3	0.008	3/4	1/4	25,000	●●●	0001656500
3	0.008	-	1/4	18,500	●○○	0009900600
3	0.014	3/4	1/4	25,000	●●●	0001656900
3	0.014	-	1/4	18,500	●○○	0009900700
4	0.008	1	1/4	15,000	●●●	0001657100
4	0.014	1	1/4	15,000	●●●	0001657200
Brass						
3	0.014	3/4	1/4	25,000	●●●	0001649700



Note: As a safety precaution, shank must be fully inserted into the chuck or collet and tightened securely.