

Rugged knot-type construction provides high brush flexibility, more uniform results, maximum safety and efficient operation at high speeds. Brushes larger than 6" should be mounted on stationary tables; those 6" and smaller can be mounted to stationary installations or attached to portable tools.

## KNOT WIRE WHEEL BRUSH

Features standard twist knot.

Brush Dia.	Plain Arbor Hole	Threaded Arbor Hole	With Bushing	Fill Dia.	Fill Material	Trim Length	Face Width	Width at Face Plates	Max RPM	Std Pk	Item No.	Clamshell
3	3/8		-	0.014	Brass	5/8	3/8	7/16	25000	12	26092	
3	3/8		-	0.014	Stainless Steel	5/8	3/8	7/16	25000	12	26206	
3	3/8		-	0.014	Steel	5/8	3/8	7/16	25000	12	26927	
3	3/8		-	0.020	Steel	5/8	3/8	7/16	25000	12	26928	26413
4	3/8		-	0.014	Stainless Steel	7/8	5/16	3/8	20000	12	26209	26211
4	3/8		-	0.014	Steel	7/8	5/16	3/8	20000	12	26017	
4	1/2		-	0.0095	Steel	7/8	5/16	3/8	20000	12	26021	
4	1/2		-	0.014	Stainless Steel	7/8	5/16	3/8	20000	12	26210	
4	5/8		1/2	0.0118	Steel	7/8	5/16	3/8	20000	12	26028	
4	5/8		1/2	0.014	Brass	7/8	5/16	3/8	20000	12	26093	
4	5/8		1/2	0.014	Stainless Steel	7/8	5/16	3/8	20000	12	26342	
4	5/8		1/2	0.014	Steel	7/8	5/16	3/8	20000	12	26029	
4	5/8		1/2	0.020	Stainless Steel	7/8	5/16	3/8	20000	12	26343	
4	5/8		1/2	0.020	Steel	7/8	5/16	3/8	20000	12	26030	
6		5/8-11NC	-	0.016	Stainless Steel	1-1/2	1/2	9/16	9000	6	26038	
6		5/8-11NC	-	0.025	Stainless Steel	1-1/2	1/2	9/16	9000	12	26346*	
6		5/8-11NC	-	0.025	Steel	1-1/2	1/2	9/16	9000	12	26047*	26110*
6	5/8		1/2	0.0095	Stainless Steel	1-1/2	1/2	9/16	9000	12	26345	
6	5/8		1/2	0.0095	Steel	1-1/2	1/2	9/16	9000	12	26040	
6	5/8		1/2	0.0118	Steel	1-1/2	1/2	9/16	9000	12	26041	
6	5/8		1/2	0.014	Steel	1-1/2	1/2	9/16	9000	12	26042	26109
6	5/8		1/2	0.016	Stainless Steel	1-1/2	1/2	9/16	9000	6	26225	26233
6	5/8		1/2	0.016	Steel	1-1/2	1/2	9/16	9000	12	26043	
6	5/8		1/2	0.025	Steel	1-1/2	1/2	9/16	9000	12	26046*	
6-1/2		5/8-11NC	-	0.025	Steel	1-1/4	3/8	9/16	9000	12	26039	
7	5/8		-	0.0118	Steel	1-3/4	5/8	9/16	9000	12	26050	26073
8	5/8		-	0.014	Steel	2-7/16	5/8	9/16	8500	12	26059	
8		5/8-11NC	-	0.016	Stainless Steel	1-11/16	5/8	9/16	8500	6	26056	
8		5/8-11NC	-	0.025	Steel	1-11/16	5/8	9/16	8500	12	26062	
8	5/8		-	0.0118	Stainless Steel	1-11/16	5/8	9/16	8500	12	26348	
8	5/8		-	0.0118	Steel	1-11/16	5/8	9/16	8500	12	26058	
8	5/8		-	0.016	Stainless Steel	1-11/16	5/8	9/16	8500	6	26230	
8	5/8		-	0.016	Steel	1-11/16	5/8	9/16	8500	12	26060	
8	5/8		-	0.025	Stainless Steel	1-11/16	5/8	9/16	8500	12	26349	
8	5/8		-	0.025	Steel	1-11/16	5/8	9/16	8500	12	26061*	
8	1-1/4		-	0.0118	Steel	1-11/16	5/8	9/16	8500	12	26064	
8	1-1/4		-	0.014	Steel	1-11/16	5/8	9/16	8500	12	26065	
8	1-1/4		-	0.016	Stainless Steel	1-11/16	5/8	9/16	8500	6	26231	
8	1-1/4		-	0.016	Steel	1-11/16	5/8	9/16	8500	12	26066	
8	1-1/4		-	0.025	Steel	1-11/16	5/8	9/16	8500	12	26067*	
10	1-1/4		-	0.0118	Steel	2-1/4	5/8	5/8	4500	6	26070	
10	1-1/4		-	0.014	Steel	2-1/4	5/8	5/8	4500	6	26071	
10	1-1/4		-	0.016	Steel	2-1/4	5/8	5/8	4500	6	26072	
12	1-1/4		-	0.0118	Steel	3-1/4	5/8	5/8	4500	6	26075	
12	1-1/4		-	0.014	Steel	3-1/4	5/8	5/8	4500	6	26076	
12	2		-	0.016	Steel	2-1/4	5/8	5/8	4500	6	26081	
15	1-1/4		-	0.016	Steel	4-1/4	3/8	11/16	4500	6	26087	
15	2		-	0.016	Steel	4-1/4	3/8	11/16	4500	6	26095	

*Applications:*  
Removal of Rubber  
Flash, Paint Slag,  
Scale, Rust, Surface  
Contamination, Weld  
Cleaning, Blending,  
Finishing, Deburring,  
Descaling, Skiving,  
Pipeline Cleaning,  
General Cleaning



**Note:** The 2" arbor hole brushes have two 1/2" x 1/4" keyways, the 1-1/4" arbor hole brushes have two 1/4" x 1/8" keyways. Other arbor hole sizes are available.



\* Cable Twist Knot