

## KNOT WIRE WHEEL BRUSH WITH SHANK

Osborn's Standard Twist Knot Wire Wheels with Shank are designed to operate at high speeds, making them fast, efficient, and thorough on a wide range of applications - including maintenance, cleaning of metals and other surfaces. All brushes have a 1/4" shank.

*Applications: Maintenance, Metal Surface Cleaning*



**Note:** As a safety precaution, shank must be fully inserted into the chuck or collet and tightened securely.

Brush Dia.	Fill Dia.	Fill Material	Trim Length	Max RPM	Item No.
3	0.014	Stainless Steel	5/8	25000	26188
3	0.014	Steel	5/8	25000	26186
3	0.020	Steel	5/8	25000	26187
4	0.014	Stainless Steel	7/8	20000	26191
4	0.014	Steel	7/8	20000	26189
4	0.020	Steel	7/8	20000	26190

## KNOT WIRE WHEEL BRUSH - HEAVY DUTY

An even harder-working design, Osborn Heavy Duty Standard Twist Knot Wire Wheel brushes have a slightly wider face width, tighter knots, and in larger sizes, a slightly shorter trim length.

*Applications: Deflashing and Cleaning Motor Mounts, Cleaning Foundry Molds, Weld Prep and Cleaning, Removing Heavy Surface Contamination, Pipeline Cleaning, Heavy-Duty Deburring*



**Note:** The 2" arbor hole brushes have two 1/2" x 1/4" keyways, the 1-1/4" arbor hole brushes have two 1/4" x 1/8" keyways. Other arbor hole sizes are available.

Brush Dia.	Plain Arbor Hole	With Bushing	Fill Dia.	Fill Material	Trim Length	Face Width	Width at Face Plates	Max RPM	Item No.	Clamshell
3	3/8	-	0.0095	Steel	11/16	3/8	1/2	25000	26003	
3	3/8	-	0.0118	Steel	11/16	3/8	1/2	25000	26004	
3	3/8	-	0.014	Stainless Steel	11/16	3/8	1/2	25000	26204	26212
3	3/8	-	0.014	Steel	11/16	3/8	1/2	25000	26005	
3	3/8	-	0.020	Steel	11/16	3/8	1/2	25000	26006	
3	1/2	-	0.0118	Steel	11/16	7/16	1/2	25000	26010	
3	1/2	-	0.014	Stainless Steel	11/16	3/8	1/2	25000	26203	
3	1/2	-	0.014	Steel	11/16	7/16	1/2	25000	26011	
3	1/2	-	0.020	Steel	11/16	7/16	1/2	25000	26012	
4	3/8	-	0.014	Stainless Steel	7/8	1/2	11/16	18000	26216	
4	3/8	-	0.014	Steel	7/8	1/2	11/16	18000	26104	
4	1/2	-	0.0118	Steel	7/8	1	11/16	18000	26250*	
4	5/8	-	0.014	Stainless Steel	7/8	1/2	11/16	18000	26218	
4	5/8	1/2	0.0118	Steel	7/8	1/2	11/16	18000	26115	
4	5/8	1/2	0.014	Steel	7/8	1/2	11/16	18000	26116	
4	5/8	1/2	0.020	Steel	7/8	1/2	11/16	18000	26117	
6	5/8	1/2	0.0118	Steel	1-1/2	1/2	5/8	9000	26121	
6	5/8	1/2	0.014	Steel	1-1/2	1/2	5/8	9000	26122	
8	5/8	-	0.0118	Steel	1-11/16	5/8	9/16	8000	26129	
8	2	-	0.020	Steel	1-11/16	5/8	9/16	8000	26240	
10	1-1/4	-	0.014	Steel	1-3/4	1/2	5/8	4500	26135	
10	1-1/4	-	0.020	Steel	1-3/4	1/2	5/8	4500	26137	
10	2	-	0.020	Steel	1-3/4	1/2	5/8	4500	26185	
12	1-1/4	-	0.014	Steel	2-1/4	1/2	11/16	5000	26234	
12	1-1/4	-	0.020	Steel	2-1/4	1/2	11/16	5000	26235	
12	2	-	0.020	Steel	2-1/4	1/2	11/16	5000	26236	
15	1-1/4	-	0.0118	Steel	2-5/8	1/2	11/16	5000	26160	
15	1-1/4	-	0.020	Steel	2-5/8	1/2	11/16	5000	26162	
15	2	-	0.020	Steel	2-5/8	1/2	11/16	5000	26167	

\* Tire Retreading and Recapping Brush