

TY ENCAPSULATED WHEEL BRUSH - MEDIUM FACE, STANDARD DUTY

Applications: Rubber Flash Removal

Brush Dia.	Plain Arbor Hole	Fill Dia.	Fill Material	Trim Length	Face Width	Width at Arbor	Max RPM	Item No.
8	2	0.008	Steel	1-1/2	31/64	33/64	4500	22773
8	2	0.0118	Steel	1-1/2	31/64	33/64	4500	22774
8	2	0.020	Steel	1-1/2	31/64	33/64	4500	22776
10	2	0.0118	Steel	2	3/4	49/64	3600	22783
12	2	0.0118	Steel	1-7/8	13/16	55/64	3000	22794



TY ENCAPSULATED WHEEL BRUSH - WIDE FACE, STANDARD DUTY

Standard duty TY elastomer gives high aggression.

Applications: Removing Paint & Coatings, Busbar Insulation Removal, Hose Skiving

Brush Dia.	Plain Arbor Hole	Fill Dia.	Fill Material	Trim Length	Face Width	Width at Arbor	Max RPM	Item No.
4-1/4	2	0.0118	Steel	3/4	7/8	13/16	6000	22701
6	2	0.008	Steel	1-1/8	1	1-1/16	6000	22703
6	2	0.0118	Steel	1-1/8	1	1-1/16	6000	22704



TY ENCAPSULATED WHEEL BRUSH - WIDE FACE, HEAVY DUTY

Heavy-duty TY elastomer gives maximum aggression for tougher applications.

Applications: Offhand Deburring, Weld Cleaning

Brush Dia.	Plain Arbor Hole	Fill Dia.	Fill Material	Trim Length	Face Width	Width at Arbor	Max RPM	Item No.
6	2	0.014	Steel	1	1	1-1/32	6000	22718

