

Osborn knot wire cup brushes are rugged, efficient tools for fast, heavy-duty cleaning of large metal surfaces. They are specially designed for use on portable tools and are filled with Osborn steel wire. Knot wire brushes are recommended for extremely rigorous jobs.

KNOT WIRE CUP BRUSH

Applications: Removal of Weld Scale, Rust, Old Paint and Corrosion, Cleaning and Surface Prep of Metals

Brush Dia.	Plain Arbor Hole	Threaded Arbor Hole	Fill Dia.	Fill Material	Rows Wide	Trim Length	Max RPM	Item No.	Clamshell
3-1/2		5/8-11NC	0.014	Brass	1	7/8	7500	33006*	
3-1/2		5/8-11NC	0.014	Stainless Steel	1	1-3/8	7500	33045*	33058
3-1/2		5/8-11NC	0.020	Steel	1	1-3/8	7500	33126	33129
3-1/2		5/8-11NC	0.020	Steel	1	1-3/8	7500	33005	
4		5/8-11NC	0.014	Steel	1	1-1/4	6000	33137	33003
4		5/8-11NC	0.020	Stainless Steel	1	1-1/4	6000	33139	33508
4		5/8-11NC	0.020	Steel	2	1	6000	33133	33140
4		5/8-11NC	0.025	Steel	1	1-1/4	6000	33138	33142
5-3/4		5/8-11NC	0.025	Steel	1	1-5/8	6000	33135	33141
6		5/8-11NC	0.014	Steel	1	1-3/4	6000	33011	33016
6		5/8-11NC	0.014	Steel	2	1-3/4	6000	33026*	
6		5/8-11NC	0.020	Stainless Steel	1	1-3/4	6000	33049	
6		5/8-11NC	0.020	Stainless Steel	2	1-3/4	6000	33134	
6		5/8-11NC	0.020	Steel	1	1-1/4	6000	33150	
6		5/8-11NC	0.020	Steel	1	1-3/4	6000	33015	33004
6		5/8-11NC	0.020	Steel	2	1-3/4	6000	33127	
6		5/8-11NC	0.020	Steel	2	1-3/4	6000	33030	
6		5/8-11NC	0.025	Steel	1	1-3/4	6000	33022	
6		5/8-11NC	0.035	Steel	1	1-3/4	6000	33021	33025
6		5/8-11NC	0.035	Steel	2	1-3/4	6000	33128	
6		5/8-11NC	0.035	Steel	2	1-3/4	6000	33034	
6	5/8		0.014	Steel	2	1-3/4	6000	33024	
6	5/8		0.020	Steel	2	1-3/4	6000	33028	
6	5/8		0.035	Steel	2	1-3/4	6000	33032	

* Heavy Duty



Adapters for mounting into smaller shafts must be specified and are priced separately. Please refer to page 51 to select the appropriate adapter.



KNOT WIRE FLARED CUP BRUSH

Has a wide diameter for wide-area cleaning, surface preparation and general maintenance.

Applications: Fast Heavy-Duty Cleaning of Large Metal Surfaces, Removal of Weld Scale, Rust, Old Paint and Corrosion, Pre-paint Surface Prep

Brush Dia.	Threaded AH	Fill Dia.	Fill Material	Rows Wide	Trim Length	Max RPM	Item No.
6	5/8-11NC	0.020	Steel	1	1-5/8	7000	26261

