CRIMPED WIRE END BRUSHES



Applications: Rubber and Plastic Mold Cleaning, Cleaning Pipe I.D., Removing Rust, Weld Scale and Spatter, Cleaning Castings, Burr Removal, Rubber Flash Removal, Carbon Removal, Spot Facing, Cleaning and Finishing Recessed Areas

CRIMPED WIRE END BRUSH

With 1/4" shank. Ideal for a variety of general uses, including surface blending, cleaning and polishing; can be used on CNC equipment. They are available with three types of wire - steel, stainless steel, and brass.

Engineered to operate at high speeds.



Note: As a safety precaution, shank must be fully inserted into the chuck or collet and tightened securely.

e with three types of whe steen, stanness steen, and brass.											
Brush	Overall	Fill	Fill	Trim	Max						
Dia.	Length	Dia.	Material	Length	RPM	Item No.	Clamshell				
3/8	2-3/4	0.006	Steel	1	25000	30091					
3/8	2-3/4	0.0104	Steel	1	25000	30092					
1/2	2-3/4	0.005	Stainless Steel	1	25000	30071	30379				
1/2	2-3/4	0.006	Steel	1	25000	30051	30370				
1/2	2-3/4	0.0104	Stainless Steel	1	25000	30019					
1/2	2-3/4	0.0104	Steel	1	25000	30053	30371				
1/2	2-3/4	0.014	Stainless Steel	1	25000	30020					
1/2	2-3/4	0.02	Steel	1	25000	30055	30372				
3/4	2-3/4	0.006	Stainless Steel	1	20000	30021					
3/4	2-3/4	0.006	Steel	1	20000	30057	30373				
3/4	2-3/4	0.0104	Stainless Steel	1	20000	30079	30380				
3/4	2-3/4	0.0104	Steel	1	20000	30059	30374				
3/4	2-3/4	0.014	Stainless Steel	1	20000	30022					
3/4	2-3/4	0.02	Steel	1	20000	30061	30375				
1	2-3/4	0.005	Stainless Steel	1	20000	30083	30381				
1	2-3/4	0.014	Brass	1	20000	30074					
1	2-7/8	0.006	Steel	1	20000	30063	30376				
1	2-7/8	0.0104	Stainless Steel	1	20000	30085	30382				
1	2-7/8	0.0104	Steel	1	20000	30065	30377				
1	2-7/8	0.014	Stainless Steel	1	20000	30025					
1	2-7/8	0.02	Steel	1	20000	30067	30378				

CRIMPED WIRE END BRUSH - SCUF-GARD COATED

Manufactured with a rugged, durable layer of elastomer on the cup to help prevent accidental scratches or marring in the work surface during operation. With 1/4" shank.



Note: As a safety precaution, shank must be fully inserted into the chuck or collet and tightened securely.

D	A	E'II	E:II	T	N 4 -	
Brush	Overall	Fill	Fill	Trim	Max	
Dia.	Length	Dia.	Material	Length	RPM	Item No.
1/2	2-3/4	0.005	Stainless Steel	1	25000	30131
1/2	2-3/4	0.006	Steel	1	25000	30116
1/2	2-3/4	0.0104	Stainless Steel	1	25000	30133
1/2	2-3/4	0.0104	Steel	1	25000	30118
3/4	2-3/4	0.006	Steel	1	20000	30121
3/4	2-3/4	0.0104	Stainless Steel	1	20000	30138
1	2-3/4	0.005	Stainless Steel	1	20000	30141
1	2-7/8	0.006	Steel	1	20000	30126
1	2-7/8	0.0104	Stainless Steel	1	20000	30143
1	2-7/8	0.0104	Steel	1	20000	30128