



BRAID OVER BRAID NYLON

Highest in value, this two in one rope has all the advantages of nylon fibers TWICE! The unique construction of a sixteen strand diamond braid jacket over an eight strand diamond braided core creates a kink free rope, ideal for marine and industrial applications where high strength along with some stretch (for shock absorbency) is a must. Available in colors. Spliceable. Some shrinkage. Resistant to most chemicals.

UPC I.D.	Diameter	Circumference	Put-up	Tensile Strength	Approx. Weight
103003	1/4"	3/4"	600'	1650	10
103010	5/16"	1"	600'	2570	16
103027	3/8"	1-1/8"	600'	3700	23
103034	7/16"	1-5/16"	600'	5020	31
103041	1/2"	1-1/2"	600'	6550	40
103089	9/16"	1-3/4"	600'	8270	50
103058	5/8"	2"	600'	10200	70
103065	3/4"	2-1/4"	600'	14700	90
103096	7/8"	2-3/4"	600'	19900	122
103072	1"	3"	600'	26000	156



BRAID OVER BRAID POLYESTER (LOW STRETCH)

An excellent choice for sheets and halyards due to its balanced and round construction, low stretch and high tensile strength. Spliceable. Available with color identification markers in blue, green, red and black.

UPC I.D.	Diameter	Circumference	Put-up	Tensile Strength	Approx. Weight
103904	1/4"	3/4"	600'	1900	11
103911	5/16"	1"	600'	2935	18
103928	3/8"	1-1/8"	600'	4245	26
103935	7/16"	1-5/16"	600'	5730	36
103942	1/2"	1-1/2"	600'	7500	47
103980	9/16"	1-3/4"	600'	9450	61
103959	5/8"	2"	600'	11660	84
103966	3/4"	2-1/4"	600'	16610	107
103977	7/8"	2-3/4"	600'	22660	147
103973	1"	3"	600'	29480	202



UNICORD COMPANIES:
 Unicord Corp., IL
 Unicord Mexico S.A. de C.V.
 Unicord International LLC
 dba Colombian Rope Co.
 Web site: www.unicordcorp.com

Corporate:
 12010 S. Paulina, St.
 Calumet Park, IL 60827
 Phone: 888-593-7999 or
 708-385-7999
 Fax: 708-385-8395



SOLID BRAID NYLON

Made of 100% Multifilament nylon with a round construction. It is ideal for blocks, pulleys, winches, mooring lines and general tie downs. Non-spliceable. Abrasion and chemical resistant. Available in colors.

UPC I.D.	Diameter	Circumference	Put-up	Tensile Strength	Approx. Weight
500000	3/32"	9/32"	1000'	337	3
500017	1/8"	3/8"	1000'	450	5
500024	5/32"	1/2"	1000'	600	7
500031	3/16"	5/8"	1000'	850	10
500048	1/4"	3/4"	1000'	1200	15
500055	5/16"	1"	1000'	1800	26
500079	3/8"	1-1/8"	1000'	2700	34
500093	1/2"	1-1/2"	500'	4000	30
500116	5/8"	2"	500'	7200	52



SOLID BRAID POLYESTER

As one of the most durable man-made fibers, polyester offers minimal shrinkage and very low stretch. Its solid braid construction allows flexibility that makes it an excellent rope for small boat sheets and halyards, flag halyards, clothesline, and general tie downs. Non-spliceable. Abrasion and chemical resistant. Available in colors.

UPC I.D.	Diameter	Circumference	Put-up	Tensile Strength	Approx. Weight
501007	3/32"	9/32"	1000'	337	3
501014	1/8"	3/8"	1000'	450	5
501021	5/32"	1/2"	1000'	800	7
501038	3/16"	5/8"	1000'	900	11
501045	1/4"	3/4"	1000'	1300	16
501052	5/16"	1"	1000'	2500	28
501069	3/8"	1-1/8"	1000'	3100	38
501083	1/2"	1-1/2"	500'	4000	32
501106	5/8"	2"	500'	7300	58



SOLID BRAID MULTIFILAMENT POLYPROPYLENE

Excellent knot retention qualities, it feels and looks like nylon at about 35% higher yield pound for pound. Various color combinations have made this particular rope a favorite of the equestrian market. Non-spliceable. Available in colors.

UPC I.D.	Diameter	Circumference	Put-up	Tensile Strength	Approx. Weight
505005	1/8"	3/8"	1000'	250	4.6
505012	3/16"	5/8"	1000'	550	10.0
505029	1/4"	3/4"	1000'	750	15.0
505036	5/16"	1"	1000'	1200	21.0
505043	3/8"	1-1/8"	1000'	1800	27.7
505050	1/2"	1-1/2"	500'	2200	18.0
505074	5/8"	2"	500'	2600	21.0