



# HONEYWELL SALISBURY ELECTRIGRIP™ DIELECTRIC FOOTWEAR

## TECHNICAL DATA SHEET

For users who depend on a single comfortable boot to provide primary protection from the risk of electric shock, Electrigrip dielectric boots provide exceptional traction along with continued confidence of safety compliance.

### CERTIFICATION AND TESTING

Standard	Description	Certification
<b>CSA Z195-14</b>	Protective Footwear	Test Voltage 20kV AC
<b>ASTM F1117</b>	Standard Specification for Dielectric Footwear	Test Voltage 20kV AC
<b>ASTM F2413</b>	Standard Specification for Performance Requirements for Protective (Safety) Toe Cap Footwear	(M I/75 C/75 PR)
<b>ASTM F2621</b>	Standard Practice for Determining Response Characteristics and Design Integrity of Arc Rated Finished Products and Evaluating other Products in an Electric Arc Exposure	Arc Flash tested to 40 cal/cm <sup>2</sup>

### PRODUCT DESCRIPTION

Model	Description	Size	Upper / Outsole Material	Lining Material	Height	Color
<b>52000</b>	Electrigrip Boot	5-16	Vulcanized Rubber	3 mm SBR foam	15"	Red / Black
<b>52001</b>	Electrigrip Thermal Boot	5-16	Vulcanized Rubber	5 mm SBR foam	15"	Red / Black

## PHYSICAL DIMENSIONS

Model	Description	Length (inches / mm)	Width (inches / mm)	Inner Throat Circumference (inches / mm)	Weight (lbs / kg)
52000 05	15" ELECTRIGRIP BOOT SZ 5	9.5 / 241.2	3.2 / 82.5	16.5 / 419.0	6.87 / 3.12
52000 06	15" ELECTRIGRIP BOOT SZ 6	9.8 / 249.6	3.3 / 84.6	16.8 / 426.0	7.12 / 3.23
52000 07	15" ELECTRIGRIP BOOT SZ 7	10.2 / 258.1	3.4 / 86.8	17.0 / 432.3	7.42 / 3.37
52000 08	15" ELECTRIGRIP BOOT SZ 8	10.5 / 266.5	3.5 / 88.9	17.3 / 438.7	7.51 / 3.41
52000 09	15" ELECTRIGRIP BOOT SZ 9	10.8 / 275.0	3.6 / 91.0	17.5 / 445.0	7.62 / 3.46
52000 10	15" ELECTRIGRIP BOOT SZ 10	11.2 / 283.5	3.7 / 93.1	17.8 / 451.4	7.84 / 3.56
52000 11	15" ELECTRIGRIP BOOT SZ 11	11.5 / 291.9	3.7 / 95.2	18.0 / 457.7	8.17 / 3.71
52000 12	15" ELECTRIGRIP BOOT SZ 12	11.8 / 300.4	3.8 / 97.4	18.3 / 464.1	8.33 / 3.78
52000 13	15" ELECTRIGRIP BOOT SZ 13	12.2 / 308.8	3.9 / 99.5	18.5 / 470.4	8.88 / 4.03
52000 14	15" ELECTRIGRIP BOOT SZ 14	12.4 / 316.0	4.0 / 101.6	18.8 / 476.8	9.10 / 4.13
52000 15	15" ELECTRIGRIP BOOT SZ 15	12.8 / 325.1	4.1 / 103.7	19.0 / 483.1	9.21 / 4.18
52000 16	15" ELECTRIGRIP BOOT SZ 16	13.1 / 332.7	4.2 / 106.7	19.3 / 489.5	9.47 / 4.30
52001 05	15" ELECTRIGRIP THERMAL BOOT SZ 5	9.5 / 241.2	3.2 / 82.5	16.5 / 419.0	7.14 / 3.24
52001 06	15" ELECTRIGRIP THERMAL BOOT SZ 6	9.8 / 249.6	3.3 / 84.6	16.8 / 426.0	7.45 / 3.38
52001 07	15" ELECTRIGRIP THERMAL BOOT SZ 7	10.2 / 258.1	3.4 / 86.8	17.0 / 432.3	7.62 / 3.46
52001 08	15" ELECTRIGRIP THERMAL BOOT SZ 8	10.5 / 266.5	3.5 / 88.9	17.3 / 438.7	7.84 / 3.56
52001 09	15" ELECTRIGRIP THERMAL BOOT SZ 9	10.8 / 275.0	3.6 / 91.0	17.5 / 445.0	8.09 / 3.67
52001 10	15" ELECTRIGRIP THERMAL BOOT SZ 10	11.2 / 283.5	3.7 / 93.1	17.8 / 451.4	8.22 / 3.73
52001 11	15" ELECTRIGRIP THERMAL BOOT SZ 11	11.5 / 291.9	3.7 / 95.2	18.0 / 457.7	8.62 / 3.91
52001 12	15" ELECTRIGRIP THERMAL BOOT SZ 12	11.8 / 300.4	3.8 / 97.4	18.3 / 464.1	9.03 / 4.10
52001 13	15" ELECTRIGRIP THERMAL BOOT SZ 13	12.2 / 308.8	3.9 / 99.5	18.5 / 470.4	9.17 / 4.16
52001 14	15" ELECTRIGRIP THERMAL BOOT SZ 14	12.4 / 316.0	4.0 / 101.6	18.8 / 476.8	9.36 / 4.25
52001 15	15" ELECTRIGRIP THERMAL BOOT SZ 15	12.8 / 325.1	4.1 / 103.7	19.0 / 483.1	9.65 / 4.38
52001 16	15" ELECTRIGRIP THERMAL BOOT SZ 16	13.1 / 333.2	4.2 / 105.8	19.3 / 489.5	9.98 / 4.53