

IMS Two-Door Enclosures

Application -

Can be bolted together in any desired multiple door arrangement.

Designed to house electrical equipment and provide degree of protection from dust, dirt, water and oil. For installation information, consult our Installation Manual at www.saginawcontrol.com.

Construction -

- 0.104" carbon steel.
- Seams continuously welded and ground smooth.
- Flange trough collar around all sides of door opening.
- Overlapping doors.
- Heavy duty lifting eyes anchor into reinforced top.
- Body stiffeners in large enclosures for extra rigidity.
- Mounting holes provided in bottom of enclosure for installing plinth base or securing to the floor.
- Concealed hinges.
- Removable and interchangeable doors.
- Black zinc die cast padlocking handle.
- 3-point latching mechanism.
- Mounting channels provided in top and bottom of enclosure.
- Oil resistant gasket.
- Enclosures are provided with provisions for mechanical interlock system expansion.
- Ground stud on door and body.
- Gland plates provided in bottom of enclosure.

Note -

SCE-IMSBK sold separately, required when bolting one enclosure to another.

Accessories - See page 183

Finish -

RAL 7035 gray powder coated inside and out.

IS3 - Industry Standards -

NEMA Type 3R, 12 & Type 13
UL Listed Type 3R & 12
CSA Type 3R & 12
IEC 60529 IP55

***Special Instructions apply for IS3, IS4 and IS6 to maintain the environmental rating of Type 3R for these parts. See the Special Instructions on the Industry Standards page in the Technical Information Section.

(IMS) INDUSTRIAL MODULAR SYSTEM TWO-DOOR ENCLOSURES

ENCLOSURE PRODUCT CODE I1

Catalog No.	Height (A)	Ref. mm Height (A)	Width (B)	Ref. mm Width (B)	Depth (C)	Ref. mm Depth (C)	Industry Standard
SCE-T181205LG	70.87	1800	47.24	1200	18.00	500	IS3
SCE-T181206LG	70.87	1800	47.24	1200	22.00	600	IS3
SCE-T181605LG	70.87	1800	62.99	1600	18.00	500	IS3
SCE-T181606LG	70.87	1800	62.99	1600	22.00	600	IS3
SCE-T201205LG	78.74	2000	47.24	1200	18.00	500	IS3
SCE-T201206LG	78.74	2000	47.24	1200	22.00	600	IS3
SCE-T201605LG	78.74	2000	62.99	1600	18.00	500	IS3
SCE-T201606LG	78.74	2000	62.99	1600	22.00	600	IS3



Phone (989) 799-6871

Fax (989) 799-4524

