

## IMS Two-Door Enclosure with Slave Door Disconnect

### Application -

Can be bolted together in any desired multiple door arrangement.

Designed to house electrical equipment and most standard type disconnects and circuit breakers, and provide degree of protection from dust, dirt, water and oil. For installation information, consult our Installation Manual at [www.saginawcontrol.com](http://www.saginawcontrol.com).

### Construction -

- 0.104" carbon steel.
- Seams continuously welded and ground smooth.
- Flange trough collar around all sides of door opening.
- Heavy duty lifting eyes anchor into reinforced top.
- Body stiffeners in large enclosures for extra rigidity.
- Mounting holes provided in bottom of enclosure for installing plinth base or securing to the floor.
- Concealed hinges.
- Removable and interchangeable doors.
- Black zinc die cast coinproof/padlocking handle on main door, padlocking on all other doors.
- 3-point latching mechanism.
- Large removable print pocket on main door of disconnect enclosures.
- Mounting channels provided in top and bottom of enclosure.
- Oil resistant gasket.
- Mechanical interlock provided on two door disconnect enclosures and all enclosures are provided with provisions for system expansion.
- Ground stud on door and body.
- Gland plates provided in bottom of enclosure.

### Note -

SCE-IMS BK sold separately, required when bolting one enclosure to another.

### Accessories - See page 185

### Finish -

RAL 7035 gray powder coated inside and out.

### IS3 - Industry Standards -

NEMA Type 3R, 12 & Type 13  
UL Listed Type 3R & 12  
CSA Type 3R & 12  
IEC 60529 IP55

\*\*\*Special Instructions apply for IS3, IS4 and IS6 to maintain the environmental rating of Type 3R for these parts. See the Special Instructions on the Industry Standards page in the Technical Information Section.

## (IMS) INDUSTRIAL MODULAR SYSTEM TWO-DOOR ENCLOSURE WITH SLAVE DOOR DISCONNECT

### ENCLOSURE PRODUCT CODE I1

Catalog No.	Height (A)	Ref. mm Height (A)	Width (B)	Ref. mm Width (B)	Depth (C)	Ref. mm Depth (C)	Industry Standard
SCE-TD181605LG	70.87	1800	62.99	1600	18.00	500	IS3
SCE-TD181606LG	70.87	1800	62.99	1600	22.00	600	IS3
SCE-TD181805LG	70.87	1800	70.87	1800	18.00	500	IS3
SCE-TD181806LG	70.87	1800	70.87	1800	22.00	600	IS3
SCE-TD201605LG	78.74	2000	62.99	1600	18.00	500	IS3
SCE-TD201606LG	78.74	2000	62.99	1600	22.00	600	IS3
SCE-TD201805LG	78.74	2000	70.87	1800	18.00	500	IS3
SCE-TD201806LG	78.74	2000	70.87	1800	22.00	600	IS3



Phone (989) 799-6871

Fax (989) 799-4524

