

## Stainless Steel Desk Consoles

### Application -

Intended for indoor use to provide a degree of protection to personnel against access to hazardous parts, also to provide a degree of protection for the equipment inside the enclosure against ingress of solid foreign objects and falling dirt, to provide a degree of protection with respect to harmful effects on the equipment due to the ingress of water, splashing water. Designed for use in a standing or sitting position with single and dual access and top that opens for easy accessibility. For installation information, consult our Installation Manual at [www.saginawcontrol.com](http://www.saginawcontrol.com).

### Construction -

- 0.075" stainless steel Type 304 & 316/316L.
- Seams continuously welded and ground smooth.
- 25 Degree Sloped top.
- Door props on sloped door to hold in the open position.
- Oil and water resistant gasket.
- Flange trough collar around all sides of door opening.
- Concealed hinges.
- Removable doors.
- Removable print pocket.
- Ground studs on door and body.
- Rubber pads with provision for leveling pads on bottom of enclosure.
- Black quarter turn latches on top door.
- Keylocking black 3-point flush swing handle in front door of single access, front and rear doors on dual access.
- Mounting studs welded on interior back for mounting optional sub-panels on single access console.
- Mounting channels welded on sides of interior body for mounting optional sub-panels on dual access console.
- Mounting hardware included for (1) optional sub-panel.

### Finish -

#4 brushed finish on all exterior surfaces. Optional sub-panels powder coated white.

### Options -

Optional tamper-resistant inserts or padlocking handles are available.

#### IS3 - Industry Standards -

NEMA Type 3R, 12 & Type 13  
UL Listed Type 3R & 12  
CSA Type 3R & 12  
IEC 60529 IP55

#### IS6 - Industry Standards -

NEMA Type 3R, 4, 4X, 12 & Type 13  
UL Listed Type 3R, 4, 4X & 12  
CSA Type 3R, 4, 4X & 12  
IEC 60529 IP66

\*\*\*Special Instructions apply for IS3, IS4 and IS6 to maintain the environmental rating of Type 3R for these parts. See the Special Instructions on the Industry Standards page in the Technical Information Section.

## 304 STAINLESS STEEL DESK CONSOLES

ENCLOSURE PRODUCT CODE S10					SUB-PANEL (P3)		
Catalog No.	Height (A)	Width (B)	Depth (C)	Industry Standard	Catalog No.	Panel Height (D)	Panel Width (E)
<b>Single Access Single-Door</b>							
SCE-402516SDCSS	40.25	25.25	15.50	IS6	SCE-30P24	27.00	21.00
SCE-403716SDCSS	40.25	37.25	15.50	IS6	SCE-36P30	33.00	27.00
SCE-462519SDCSS	46.25	25.25	18.50	IS6	SCE-36P24	33.00	21.00
SCE-463719SDCSS	46.25	37.25	18.50	IS3	SCE-36P36	33.00	33.00
<b>Dual Access Single-Door</b>							
SCE-462519DCSS	46.25	25.25	18.50	IS6	SCE-36P24	33.00	21.00
SCE-463719DCSS	46.25	37.25	18.50	IS3	SCE-36P36	33.00	33.00
<b>Single Access Overlapping Two-Door</b>							
SCE-464919SDCSS	46.25	49.25	18.50	IS3	SCE-48P36	45.00	33.00
SCE-466019SDCSS	46.25	59.88	18.50	IS3	SCE-60PC36	55.63	33.00
<b>Dual Access Overlapping Two-Door</b>							
SCE-464919DCSS	46.25	49.25	18.50	IS3	SCE-48P36	45.00	33.00
SCE-466019DCSS	46.25	59.88	18.50	IS3	SCE-60PC36	55.63	33.00
<b>Dual Access Two-Door With Center Channel</b>							
SCE-464919DCCSS	46.25	49.25	18.50	IS6	SCE-48P36	45.00	33.00
SCE-466019DCCSS	46.25	59.88	18.50	IS6	SCE-60PC36	55.63	33.00

## 316 STAINLESS STEEL DESK CONSOLES

ENCLOSURE PRODUCT CODE S7					SUB-PANEL (P3)		
Catalog No.	Height (A)	Width (B)	Depth (C)	Industry Standard	Catalog No.	Panel Height (D)	Panel Width (E)
<b>Single Access Single-Door</b>							
SCE-402516SDCSS6	40.25	25.25	15.50	IS6	SCE-30P24	27.00	21.00
SCE-403716SDCSS6	40.25	37.25	15.50	IS3	SCE-36P30	33.00	27.00
SCE-462519SDCSS6	46.25	25.25	18.50	IS6	SCE-36P24	33.00	21.00
SCE-463719SDCSS6	46.25	37.25	18.50	IS3	SCE-36P36	33.00	33.00
<b>Dual Access Single-Door</b>							
SCE-462519DCSS6	46.25	25.25	18.50	IS6	SCE-36P24	33.00	21.00
SCE-463719DCSS6	46.25	37.25	18.00	IS3	SCE-36P36	33.00	33.00
<b>Single Access Overlapping Two-Door</b>							
SCE-464919SDCSS6	46.25	49.25	18.50	IS3	SCE-48P36	45.00	33.00
SCE-466019SDCSS6	46.25	59.88	18.50	IS3	SCE-60PC36	55.63	33.00
<b>Dual Access Overlapping Two-Door</b>							
SCE-464919DCSS6	46.25	49.25	18.50	IS3	SCE-48P36	45.00	33.00
SCE-466019DCSS6	46.25	59.88	18.50	IS3	SCE-60PC36	55.63	33.00
<b>Dual Access Two-Door With Center Channel</b>							
SCE-464919DCCSS6	46.25	49.25	18.50	IS6	SCE-48P36	45.00	33.00
SCE-466019DCCSS6	46.25	59.88	18.50	IS6	SCE-60PC36	55.63	33.00

