

Enviroline® Series Trough Junction Enclosures

Application -

Designed to house electrical controls, instruments and components used in an indoor or outdoor environment to provide a degree of protection for the equipment inside the enclosure against ingress of solid foreign objects (falling dirt); and provide a degree of protection with respect to the harmful effects on the equipment due to the ingress of water (rain, sleet, snow). For installation information, consult our Installation Manual at www.saginawcontrol.com.

Construction -

- 0.063" stainless steel Type 304.
- Seams continuously welded and ground smooth.
- Flange trough collar around all sides of door opening.
- Oil-resistant gasket.
- Standoffs provided for mounting optional sub-panels.
- Removable hinges.
- Doors open 180 degrees.
- Black mini quarter turn latches.
- Latches are opened or closed with a screwdriver.
- Sealing washers and hole plugs included.
- Ground stud on door and body.
- Mounting feet included.
- Padlocking or keylocking latches, and tamper-resistant hardware is available.

Finish -

#4 brushed finish on all exterior surfaces. Optional sub-panels powder coated white.


IS6 - Industry Standards -

NEMA Type 3R, 4, 4X, 12 & Type 13
UL Listed Type 3R, 4, 4X & 12
CSA Type 3R, 4, 4X & 12
IEC 60529 IP66

***Special Instructions apply for IS3, IS4 and IS6 to maintain the environmental rating of Type 3R for these parts. See the Special Instructions on the Industry Standards page in the Technical Information Section.

STAINLESS STEEL ENVIROLINE® SERIES TROUGH JUNCTION ENCLOSURES

ENCLOSURE PRODUCT CODE S6					SUB-PANEL (P3)		
Catalog No.	Height (A)	Width (B)	Depth (C)	Industry Standard	Catalog No.	Panel Height (E)	Panel Width (F)
SCE-L9126ELJSS	9.00	12.00	6.00	IS6	SCE-9P12L	8.00	11.00
SCE-L9128ELJSS	9.00	12.00	8.00	IS6	SCE-9P12L	8.00	11.00
SCE-L9186ELJSS	9.00	18.00	6.00	IS6	SCE-9P18L	8.00	17.00
SCE-L9188ELJSS	9.00	18.00	8.00	IS6	SCE-9P18L	8.00	17.00
SCE-L9246ELJSS	9.00	24.00	6.00	IS6	SCE-9P24L	8.00	23.00
SCE-L9248ELJSS	9.00	24.00	8.00	IS6	SCE-9P24L	8.00	23.00
SCE-L9306ELJSS	9.00	30.00	6.00	IS6	SCE-9P30L	8.00	29.00
SCE-L9308ELJSS	9.00	30.00	8.00	IS6	SCE-9P30L	8.00	29.00
SCE-L9366ELJSS	9.00	36.00	6.00	IS6	SCE-9P36L	8.00	35.00
SCE-L9368ELJSS	9.00	36.00	8.00	IS6	SCE-9P36L	8.00	35.00



Phone (989) 799-6871
Fax (989) 799-4524

SCE SAGINAW
CONTROL &
ENGINEERING
Your Enclosure Source®