

ENVIRO-THERM® THERMAL MANAGEMENT

Fan Heater with Thermostat

Designed to protect electrical controls, instruments and sensitive components from low temperatures and the effects of condensation and corrosion by maintaining a stable temperature within the electrical enclosure. These heaters are not intended for use in hazardous, wet, dusty or dirty locations. For installation information, consult our Installation Manual at www.saginawcontrol.com.

IS24 - Industry Standards
UL Component Recognized

Fan Heater

Compact design that heats up dynamically and is quiet during operation. Din rail clip design for 15mm, 35mm and C-Din Rail. 14" heater cable, 10" fan cable. 100 - 240V 50/60 Hz Heater and 24 V Integrated fan. For installation information, consult our Installation Manual at www.saginawcontrol.com.

IS24 - Industry Standards
UL Component Recognized

Touch Safe Heater

PTC (Positive Temperature Coefficient) Din rail clip design for 35mm Din Rail. Designed for protection from low temperatures, condensation and corrosion. Touch Safe with 2 screw terminal for standard AWG 14 wire. 110 - 240V AC or DC. For installation information, consult our Installation Manual at www.saginawcontrol.com.


IS24 - Industry Standards
UL Component Recognized

Catalog No.	Watt @ 60 Hz	Volt	Height	Width	Depth	Product Code
SCE-HF1251A	125	115	5.50	4.00	4.50	P1
SCE-HF1252A	125	230	5.50	4.00	4.50	P1
SCE-HF2001A	200	115	5.50	4.00	4.50	P1
SCE-HF2002A	200	230	5.50	4.00	4.50	P1
SCE-HF4001B	400	115	7.50	4.00	4.50	P1
SCE-HF4002B	400	230	7.50	4.00	4.50	P1
SCE-HF8001B	800	115	7.50	4.00	4.50	P1
SCE-HF8002B	800	230	7.50	4.00	4.50	P1



- Brushed Aluminum Housing
- Thermostat Range 0° to 100°F (-18° to 38°C)
- Heat discharge at the top of the heater
- Panel mount
- Air volume of 16 CFM on 125 & 200 Watt heaters, 26 CFM on 400 & 800 Watt heaters
- Heat indicator light
- Switch for Auto or Fan
- UL Recognized
- CSA Approved
- CE

Catalog No.	Watts	Max Current	Height	Width	Depth	Product Code
SCE-H350	350	3.0 A	3.10	2.10	3.30	P1



Catalog No.	Watts	Max Current	Height	Width	Depth	Product Code
SCE-TSH25	25	2.5 A	4.92	1.61	1.61	P1
SCE-TSH50	50	3.5 A	4.92	1.61	1.61	P1
SCE-TSH75	75	4.0 A	5.51	2.76	2.48	P1
SCE-TSH100	100	5.0 A	5.51	2.76	2.48	P1
SCE-TSH150	150	9.5 A	8.66	2.76	2.48	P1



Phone (989) 799-6871
Fax (989) 799-4524

SCE SAGINAW
CONTROL &
ENGINEERING
Your Enclosure Source®