

PROTECTIVE ACCESS ENCLOSURES

Hinged Window Enclosure

Designed to mount on the exterior of an enclosure to provide protection for controls with easy access. ELJ hinges. Black mini quarter turn latches. UV stable Polycarbonate viewing window. Gasket and hardware included. Made of heavy gauge carbon steel and powder coated. "SS" parts made of heavy gauge stainless steel Type 304 with #4 brushed finish.

Recommend use as Type 3R rating in full outdoor exposure and extreme weather environments – the addition of ventilation is necessary to handle the large negative pressure differential caused in a tightly sealed enclosure in extreme weather conditions. Temperatures that may exceed 140°F, such as outdoor in direct sunlight should be evaluated, shading or sun shield may be necessary.

For more details see *Design Considerations When Specifying Your Enclosure* on our website.

IS3 - Industry Standards -
NEMA Type 3R, 12 & Type 13
UL Listed Type 3R & 12
CSA Type 3R & 12
IEC 60529 IP55

IS4 - Industry Standards -
NEMA Type 3R, 4, 12 & Type 13
UL Listed Type 3R, 4 & 12
CSA Type 3R, 4 & 12
IEC 60529 IP66

IS6 - Industry Standards -
NEMA Type 3R, 4, 4X, 12 & Type 13
UL Listed Type 3R, 4, 4X & 12
CSA Type 3R, 4, 4X & 12
IEC 60529 IP66

Hinged Access Enclosure

Designed to house electrical controls, instruments and components used in an indoor or outdoor environment to provide a degree of protection for the equipment inside the enclosure against ingress of solid foreign objects (falling dirt); and provide a degree of protection with respect to the harmful effects on the equipment due to the ingress of water (rain, sleet, snow). ELJ hinges. Black mini quarter turn latches. Gasket and hardware included.


IS4 - Industry Standards -
NEMA Type 3R, 4, 12 & Type 13
UL Listed Type 3R, 4 & 12
CSA Type 3R, 4 & 12
IEC 60529 IP66

IS6 - Industry Standards -
NEMA Type 3R, 4, 4X, 12 & Type 13
UL Listed Type 3R, 4, 4X & 12
CSA Type 3R, 4, 4X & 12
IEC 60529 IP66


| Catalog No. | Height (A) | Width (B) | Depth (C) | Number Windows | Viewing Area Height x Width | Industry Standard | Product Code |
|---------------|------------|-----------|-----------|----------------|-----------------------------|-------------------|--------------|
| SCE-HWK1212 | 12.00 | 12.00 | 1.50 | 1 | 8.00 x 7.38 | IS4 | P6 |
| SCE-HWK1814 | 18.00 | 14.00 | 1.50 | 1 | 14.00 x 9.38 | IS4 | P6 |
| SCE-HWK2218 | 22.00 | 18.00 | 1.50 | 1 | 18.00 x 13.38 | IS3 | P6 |
| SCE-HWK2228 | 22.00 | 28.00 | 1.50 | 2 | 18.00 x 10.56 | IS3 | P6 |
| SCE-HWK2822 | 28.00 | 22.00 | 1.50 | 2 | 10.88 x 17.38 | IS3 | P6 |
| SCE-HWK1212LG | 12.00 | 12.00 | 1.50 | 1 | 8.00 x 7.38 | IS4 | P6 |
| SCE-HWK1814LG | 18.00 | 14.00 | 1.50 | 1 | 14.00 x 9.38 | IS4 | P6 |
| SCE-HWK2218LG | 22.00 | 18.00 | 1.50 | 1 | 18.00 x 13.38 | IS3 | P6 |
| SCE-HWK2228LG | 22.00 | 28.00 | 1.50 | 2 | 18.00 x 10.56 | IS3 | P6 |
| SCE-HWK2822LG | 28.00 | 22.00 | 1.50 | 2 | 10.88 x 17.38 | IS3 | P6 |

Stainless Steel


| | | | | | | | |
|---------------|-------|-------|------|---|---------------|-----|----|
| SCE-HWK1212SS | 12.00 | 12.00 | 1.50 | 1 | 8.00 x 7.38 | IS6 | P6 |
| SCE-HWK1814SS | 18.00 | 14.00 | 1.50 | 1 | 14.00 x 9.38 | IS6 | P6 |
| SCE-HWK2218SS | 22.00 | 18.00 | 1.50 | 1 | 18.00 x 13.38 | IS3 | P6 |
| SCE-HWK2228SS | 22.00 | 28.00 | 1.50 | 2 | 18.00 x 10.56 | IS3 | P6 |
| SCE-HWK2822SS | 28.00 | 22.00 | 1.50 | 2 | 10.88 x 17.38 | IS3 | P6 |



SCE-HWK1212(SS)
SCE-HWK1814(SS)
SCE-HWK2218(SS)



SCE-HWK2228(SS)



SCE-HWK2822(SS)

| Catalog No. | Height (A) | Width (B) | Depth (C) | Finish | Industry Standard | Product Code |
|---------------|------------|-----------|-----------|---------------|-------------------|--------------|
| SCE-HA1010 | 10.00 | 10.00 | 1.50 | ANSI-61 Gray | IS4 | P6 |
| SCE-HA1212 | 12.00 | 12.00 | 1.50 | ANSI-61 Gray | IS4 | P6 |
| SCE-HA1814 | 18.00 | 14.00 | 1.50 | ANSI-61 Gray | IS4 | P6 |
| SCE-HA1010-05 | 10.00 | 10.00 | 1.50 | SCE-05 White | IS4 | P6 |
| SCE-HA1212-05 | 12.00 | 12.00 | 1.50 | SCE-05 White | IS4 | P6 |
| SCE-HA1010LG | 10.00 | 10.00 | 1.50 | RAL 7035 Gray | IS4 | P6 |
| SCE-HA1212LG | 12.00 | 12.00 | 1.50 | RAL 7035 Gray | IS4 | P6 |
| SCE-HA1814LG | 18.00 | 14.00 | 1.50 | RAL 7035 Gray | IS4 | P6 |

Stainless Steel

| | | | | | | |
|--------------|-------|-------|------|-------------------|-----|----|
| SCE-HA1010SS | 10.00 | 10.00 | 1.50 | #4 Brushed Finish | IS6 | P6 |
| SCE-HA1212SS | 12.00 | 12.00 | 1.50 | #4 Brushed Finish | IS6 | P6 |
| SCE-HA1814SS | 18.00 | 14.00 | 1.50 | #4 Brushed Finish | IS6 | P6 |



1 Operator System Enclosures
 2 Wall-Mount Enclosures
 3 Free-Standing & Floor-Mounted Enclosures
 4 Modular Enclosures
 5 Operator System Enclosures (Stainless Steel)
 6 Wall-Mount Enclosures (Stainless Steel)
 7 Free-Standing & Floor-Mounted Enclosures (Stainless Steel)
 8 Non-Metallic Enclosures
 9 Protective Access Enclosures
 10 Technical Information
 11 Index