



The Hang-A-Light® String Light Series is ideal for applications requiring overhead temporary high-output lighting over long distances. The 14/2, 14/3 and 12/3 cords have 5 or 10 sockets with up to 14 watts per socket and are spaced every 5 or 10 feet with plastic or metal cages for bulb protection. Bright and dependable, Hang-A-Light® delivers maximum light output in a durable package with no hot surfaces.

- Protective Plastic Cage
- Energy Efficient
- No Hot Surfaces
- Link Strings Together*

Model No.	Lumens	Lighting Range	Bulb Type	Lamp Life (hrs)	Kelvins	Watts	Amp Draw	Voltage	Linking Units	Tested	Cord Type	Weight
11107050	N/A	50 ft	N/A	N/A	N/A	14 x5	N/A	120V	8	UL	14/3 SJTW	10 lbs
11107100	N/A	100 ft	N/A	N/A	N/A	14 x10	N/A	120V	5	UL	14/3 SJTW	20 lbs
11108100	N/A	100 ft	N/A	N/A	N/A	14 x10	N/A	120V	N/A	UL	14/2 SJTW	20 lbs

*Only on Models 11107050 & 11107100



LED / 111917

- Protective Plastic Cage
- Energy efficient
- No Hot Surfaces
- Durable LED Bulbs
- Link Strings Together
- 14/3 SJTW Cord


Model No.	Lumens	Lighting Range	Bulb Type	Lamp Life (hrs)	Kelvins	Watts	Amp Draw	Voltage	Linking Units	Tested	Cord Type	Weight
131050	1,500 x5	50 ft	LED	30,000	5,000	14 x5	.64	120V	8	UL	14/3 SJTW	10 lbs
131100	1,500 x10	100 ft	LED	30,000	5,000	14 x10	1.27	120V	5	UL	14/3 SJTW	20 lbs
111100	1,500 x10	100 ft	LED	30,000	5,000	14 x10	1.27	120V	N/A	UL	14/2 SJTW	20 lbs

- Protective Metal Cage
- Energy efficient
- No Hot Surfaces
- Durable LED Bulbs Available
- Link up to 5 Strings
- 12/3 SJTW Cord



Model No.	Lumens	Lighting Range	Bulb Type	Lamp Life (hrs)	Kelvins	Watts	Amp Draw	Voltage	Linking Units	Tested	Cord Type	Weight
11109050	N/A	50 ft	N/A	N/A	N/A	14 x5	N/A	120V	5	cUL	12/3 SJTW	13 lbs
11109100	N/A	100 ft	N/A	N/A	N/A	14 x10	N/A	120V	5	cUL	12/3 SJTW	28 lbs

- Protective Metal Cage
- Energy efficient
- No Hot Surfaces
- Durable LED Bulbs
- Link Strings Together
- 12/3 SJTW Cord



LED / 111917

Model No.	Lumens	Lighting Range	Bulb Type	Lamp Life (hrs)	Kelvins	Watts	Amp Draw	Voltage	Linking Units	Tested	Cord Type	Weight
121050	1,500 x5	50 ft	LED	30,000	5,000	14 x5	.64	120V	8	cUL	12/3 SJTW	13 lbs
121100	1,500 x10	100 ft	LED	30,000	5,000	14 x10	1.27	120V	5	cUL	12/3 SJTW	28 lbs